

# FONTAINE

## DETACHABLE DOUBLE DROP EXTENDABLE

MODEL: RENEGADELXT40 (Renegade LXT40 Air Tandem)

2018

574169 - 574172

Capacity:	40 Tons in 16' length – GAWR and tire ratings determine legal loads
Load Base:	16' rigid 2-point load centered in deck
Framework:	All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs
Compatibility:	Designed to accept optional flip neck extension and third flip axle
Length/width:	47 feet 11 inches **see deck length options – 102 inches wide
Gooseneck Design:	Mechanical removable with removable fifth wheel guide rollers – combination figure – 8 plate which provides 50 inches and 52 inches loaded – swing radius of 81 inches
Gooseneck platform:	Full width gooseneck platform with 1 1/8 inch wood floor
Flip box:	None
Tool box:	None
Gooseneck fenders:	Aluminum fenders at rear of gooseneck
Electrical Receptacle:	J560 7-pin connector
Deck Design:	Flat level telescopic deck design
Deck Length:	34 feet 0 inches clear deck length (retracted) – 60 feet 0 inches (extended) **Note trailer overall length is 53 feet
Loaded Deck Height:	20" with 6" ground clearance
Flooring:	1 3/8" nominal wood (full width)
Recessed Floor Mounted D-Ring	None
Package:	
Crossmembers:	On 24" centers
Front Ramps:	None, front of deck sloped top down to assist in loading with traction cleats
Extension Brackets:	Mounting brackets only
Front Bogie Ramp:	Sloped steel bogie ramp (full width)
Mini Boom Trough & traction Cleats:	None
Deck to Bogie Connection:	Fixed
Number of Axles:	2
Axle Capacity:	25,000# nominal capacity per axle Note: GAWR determined by suspension type, brakes, tires and other components
Axle Spread:	54.5" spread (between axles)
Brakes:	16.5" x 7" with 5.5" auto slacks – heavy duty brake drums – outboard mount
Dust Shields:	None
Spring Brakes:	Spring brakes on 2 axles
Suspension:	Air ride with automatic controls
First axle lift:	Chain lift included on first axle when 34ft deck is selected
Tires:	255/70R 22.5 H ply OEM standard
Wheels:	8.25 x 22.5 steel disc - hub piloted
Covered Rear Bogie:	Rear bogie platform with 1 1/8" wood floor
Rear Bogie Height:	41"
Bumper:	3 tail light package
Connections for Future Axle	Air and electrical connections to go along with connecting ears
Attachment:	
Width:	8' 6"
Electrical System:	DOT sealed beam and harness with LED lights
Flip Axle:	None
Dust shields on flip axle:	None

### DISCLAIMER

SPECIFICATIONS ARE BELIEVED TO BE CORRECT, BUT MAY CONTAIN ERRORS AND/OR OMISSIONS. PHOTOGRAPHS ARE REPRESENTATIVE OF THE SUBJECT EQUIPMENT, BUT MAY NOT BE IDENTICAL. EQUIPMENT AVAILABILITY, PRICES AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Flip Axle Strobe Light Kit:	None
Paint:	Fontaine BLACK polyurethane enamel
Lash Rings:	9 Pair – 18 Total
Flag Holders:	3 pair flag holders
ABS:	4S/2M system without diagnostic tool and cable
Liquid Filled Gauge:	Included
Marker Lights:	8 Marker lights per side including mid-turn
Accent Package:	Stainless steel accent package
VIN Plate:	Bilingual VIN plate
Registration/ Document Holder:	Install registration/document holder
Estimated Weight:	21,315# +/-3%

**DISCLAIMER**

SPECIFICATIONS ARE BELIEVED TO BE CORRECT, BUT MAY CONTAIN ERRORS AND/OR OMISSIONS.  
PHOTOGRAPHS ARE REPRESENTATIVE OF THE SUBJECT EQUIPMENT, BUT MAY NOT BE IDENTICAL.  
EQUIPMENT AVAILABILITY, PRICES AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.