

# FONTAINE

## Specifications

### Extendable 53' – 90' MODEL XTP5390SA2- Air Slider Tandem

2017

574217 - 574231

Overall Length:	53' to 90' – adjustable w/locks approx. every 5'; 102" wide
Suspension Type:	Sliding air tandem
Frame Rating:	80,000# distributed – self-supporting, properly blocked
Flooring:	1 1/8" wood
Crossmembers:	12" centers – 4" Jr. I-steel
Side Rails:	6" structural channel @ 6.5 lbs/ft
Stake Pockets:	3/16" steel on 24" centers
Rubrail:	2 1/2" x 3/8" thick HD mill formed steel
Main Beams:	Minimum grade 80 flanges
Air/Electrical @ Ext Locks:	Inside Track System
Kingpin:	24"
Loaded 5 <sup>th</sup> Wheel Height:	49"
Landing Gear:	OEM standard
Bulkhead:	None
Bulkhead Pockets:	(4) F-5 DOT type steel
Number of Axles:	2
Axle Spindle:	Tapered
Brakes:	Spring brakes, auto slacks
Dust Shields:	None
ABS:	2S/1M – no cable or tool
Axle Spread:	49"
Hub & Drums:	10-Hole hub piloted w/outboard cast drums
Wheel Ends:	Grease in hubs
Wheels:	22.5 x 8.25 steel disc wheels pre-painted white
Tires:	11R 22.5 economical, OEM standard
Suspension Detail:	Hendrickson air ride on slide box – 60" adjustable
Front Corners:	Tapered
Electrical System:	Sealed Harness – with LED lights: 3 lights/side, 2 lights/side on rear
Paint:	<b>BLACK</b> urethane
Conspicuity Tape:	Per NHTSA specs – installed on rub rail
Bumper:	Meets underride requirements
Mudflaps:	1-set Fontaine
Winch Track:	Full length – steel on road side
Sliding Winches:	12 – without straps
Winch Straps:	None
Hubodometer:	None
Registration/Document Holder:	Install registration/document holder
Tool Box:	None
VIN Plate:	US VIN plate
Weight:	18,810# +/-3%

#### Disclaimer

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are representative of the subject equipment, but may not be identical. Equipment availability, prices and specifications are subject to change without notice.