

FONTAINE

DETACHABLE DOUBLE DROP EXTENDABLE

MODEL: RENEGADELXT40 (Renegade LXT40 Air Tandem)

2018

574699-574704

| | |
|-------------------------------------|--|
| Capacity: | 40 Tons in 16' length – GAWR and tire ratings determine legal loads |
| Load Base: | 16' rigid 2-point load centered in deck |
| Framework: | All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs |
| Compatibility: | Designed to accept optional flip neck extension and third flip axle |
| Length/width: | 47 feet 11 inches **unless 34 60 deck length selected then overall length is 53 – 102 inches wide |
| Gooseneck Design: | Mechanical removable with removable fifth wheel guide rollers – combination figure – 8 plate which provides 50 inches and 52 inches loaded – swing radius of 81 inches |
| Gooseneck platform: | Full width gooseneck platform with 1 1/8 inch wood floor |
| Flip box: | None |
| Tool box: | None |
| Gooseneck fenders: | Aluminum fenders at rear of gooseneck |
| Electrical Receptacle: | J560 7-pin connector |
| Deck Design: | Flat level telescopic deck design |
| Deck Length: | 29' clear deck length (retracted) – 50' (extended) |
| Loaded Deck Height: | 20" with 6" ground clearance |
| Flooring: | 1 3/8" nominal wood (full width) |
| Recessed Floor Mounted D-Ring | None |
| Package: | |
| Crossmembers: | On 24" centers |
| Front Ramps: | None, front of deck sloped top down to assist in loading with traction cleats |
| Extension Brackets: | Mounting brackets only |
| Front Bogie Ramp: | Sloped steel bogie ramp (full width) |
| Mini Boom Trough & traction Cleats: | None |
| Deck to Bogie Connection: | Fixed |
| Number of Axles: | 2 |
| Axle Capacity: | 25,000# nominal capacity per axle Note: GAWR determined by suspension type, brakes, tires and other components |
| Axle Spread: | 54.5" spread (between axles) |
| Brakes: | 16.5" x 7" with 5.5" auto slacks – heavy duty brake drums – outboard mount |
| Dust Shields: | None |
| Spring Brakes: | Spring brakes on 2 axles |
| Suspension: | Air ride with automatic controls |
| First axle lift: | Chain lift included on first axle when 34ft deck is selected |
| Tires: | 255/70R 22.5 H ply OEM standard |
| Wheels: | 8.25 x 22. 5 steel disc - hub piloted |
| Covered Rear Bogie: | Rear bogie platform with 1 1/8" wood floor |
| Rear Bogie Height: | 41" |
| Bumper: | 3 tail light package |
| Connections for Future Axle | Air and electrical connections to go along with connecting ears |
| Attachment: | |
| Width: | 8' 6" |
| Electrical System: | DOT sealed beam and harness with LED lights |

DISCLAIMER

SPECIFICATIONS ARE BELIEVED TO BE CORRECT, BUT MAY CONTAIN ERRORS AND/OR OMISSIONS. PHOTOGRAPHS ARE REPRESENTATIVE OF THE SUBJECT EQUIPMENT, BUT MAY NOT BE IDENTICAL. EQUIPMENT AVAILABILITY, PRICES AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

| | |
|--------------------------------|--|
| Flip Axle: | None |
| Dust shields on flip axle: | None |
| Flip Axle Strobe Light Kit: | None |
| Paint: | Fontaine BLACK polyurethane enamel |
| Lash Rings: | 9 Pair – 18 Total |
| Flag Holders: | 2 pair flag holders |
| ABS: | 4S/2M system without diagnostic tool and cable |
| Liquid Filled Gauge: | Included |
| Marker Lights: | 8 Marker lights per side including mid-turn |
| Accent Package: | Stainless steel accent package |
| VIN Plate: | Bilingual VIN plate |
| Registration/ Document Holder: | Install registration/document holder |
| Estimated Weight: | 20,130# +/-3% |

DISCLAIMER

SPECIFICATIONS ARE BELIEVED TO BE CORRECT, BUT MAY CONTAIN ERRORS AND/OR OMISSIONS.
PHOTOGRAPHS ARE REPRESENTATIVE OF THE SUBJECT EQUIPMENT, BUT MAY NOT BE IDENTICAL.
EQUIPMENT AVAILABILITY, PRICES AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.