



Hale Trailer Brake & Wheel 941022



Item	Qty	Description
AT-95		<p>Overall length 45'- Overall Height 13'3"</p> <p>Top Rail-5"x4"x1/4" x 40', 40' 8" I-Beam Full Length of Trailer</p> <p>Sidewalls 3/16" Abrasion Resistant Steel</p> <p>Floor- 3/16" USS – 3x2 Rectangular Tubing cross members on 16" centers,</p> <p>5x3" Rectangular Tubing Vertical Side Braces – 24" centers</p> <p>Curb Side Hinged Rear Door with Manual Ratchet Locks & Safety Chain</p> <p>Door within a door, for connecting to customers existing compactors (Need Dimensions)</p> <p>8 1/2" Dia. hydraulic double acting ejection cylinders with carriage member</p> <p>Cylinder Mounted on "T track" in center of body floor running full length of trailer</p> <p>1.800 PSI operating pressure, Pilot check valve for quick return,</p> <p>King pin 30" center 3/8" plate reinforced, L.E.D Lights meet dot # 108 – Reflective DOT tape</p> <p>Heavy-duty 120,000# landing gear two speed</p> <p>Hutch 9700 Three-Leaf Suspension (Tandem axle), 25,000 lbs. Meritor Axles</p> <p>(8) 11R22.5 Tires w/ 10-hole Uni-mount rims (Steel)</p> <p>Anti lock brake system, on 16 1/2 x 7 brakes</p> <p>Cleaned, Primed, Painted with Industrial Enamel w/ Hardener</p> <p>(1) Year Manufacturers Warranty</p>
RCA-215T	1	Ridewell 20k Air Lift Axle (Non-Steerable) -11R22.5 Tire & 10-Hole Uni-mount Rim (Single)
72-1001	2	11R22.5 Tire & 10-Hole Unimount Wheel (Steel)
Hardox- ...	1	Upgrade to Hardox AR450 3/16" Plate for AT-95 Transfer Trailer

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.