

TK120ES, 58' X 10'

TK120ES, 58' X 10' wide 120,000 distributed 100,000 in 10' (closed) 10' narrow gooseneck, with 48" flip neck section 50" loaded 5th wheel height (3) axle air ride suspension, with 60" axle spacing 31" loaded deck height 1 3/8" apitong decking 10" mill channel side rail 3/8" X 2" rub rail with pipe spools Frame reinforced for tandem axle booster, with brackets and connections 235/75R X 17.5 tires on 8 hole pilot mount steel disc wheels L.E.D. light package Three tail light package 4-way socket in light channel LBS. (3/4" wall) axles Black In color with white decals

To be compatable with flip axle and booster extension from 120HED SN# 8M072259, 8M02261 Also goes with D1960, D1961, D1961S, D1963, D1964, D1964S, D1966, D1967, D1967S

Double pipe spools in lieu of standard Additional side clearance lights (per pair) (5 pair maximum)

XOXOX
X -Clearance Lights

O = Mid Turn Signal

62923 96" gooseneck flip extension for 10' wide TK120ES

Mid-tum signal (per pair)

Fixed 4th axle for 120ES #62922, Increases OAL trailer length, trailer still reinforced for 2AB Brackets only for Removable oversized load sign

PSI Tire Inflation System for tri-axles

One pair of 4" round amber strobes at rear ILO 3rd tail light w/switch

Additional D-rings (Ea.) 8 pair on top of bottom flange for overwidth loads (main deck)

#63131 • Shim kit for flip neck sections

All wheel area and connections on the 120HED's and the 120ES's need to be the same so all axles and booster extentions are compatible with current and previous trailer and that has been discussed with Eng

Axle track tone 98" ILO 95"