



OAL: 58' 6"

OAW: 102"

Hale Trailer Brake & Wheel A000014

OAW: 102"

MODEL: XL 60HDGSM

DIST: 60,000#

CONC. 45,000# IN 16'

WEIGHT +/-3%

GOOSENECK-

LENGTH: 12' SCRAPER NECK
KING PIN SETTING: 16"
SWING CLEARANCE: 98"
5TH WHEEL HEIGHT: 49" W/ 5 VARIABLE RIDE HEIGHT POSITIONS
HYDRAULICS: 13HP HONDA POWER UNIT WITH STEEL COVER - DUAL HYDRAULICS

MAIN DECK-

LENGTH: 3 BEAM DESIGN - 3 1/8" CHAMBER (PLUS OR MINUS 3/4")
32" WITH 31' 6" OF CLEAR DECK
LOADED DECK HGT: 12" W 4" GROUND CLEARANCE
DECKING: STEEL DECKING BETWEEN MAIN BEAMS WITH DURABAK
1 1/8" APITONG DECKING, FLUSH BETWEEN MAIN BEAMS AND OUTER BEAMS
CROSSMEMBER: 4" JR. I-BEAM ON 18" CENTERS
SIDE BEAMS: FAB I-BEAMS 8"
D-RINGS: 12 BENT D-RINGS PER SIDE- 24 TOTAL
RAMPS: TAPERS TO 4"
OUTRIGGERS: NONE

REAR DECK:

LENGTH: 14' 6"
LOADED DECK HEIGHT: 40"
AXLES: (3) 25,000 NOMINAL, 77 1/2" TRACKING
SUSPENSION: HEND-TURNER / 25,000 AIR
AXLE SPACING: 60"
ABS: 4S2M WITH SPRING BRAKES ON 2 AXLES
TIRES: 255 / 70R / 22.5
WHEELS: 8.25 X 22.5 ALUMINUM MILLED INSIDE, ALUMINUM POLISHED OUTSIDE DISC WHEELS
BRAKES: 16 1/2" X 7"
DRUMS: HUB PILOT / OUTBOARD DRUMS
ELECTRICAL: 12V SEALED GROTE SYSTEM WITH 3 TAIL LIGHT ALUMINUM PACKAGE
4" AMBER STROBE WITH SWITCH TO MAKE 3 STT
DECKING: 1 1/8" APITONG DECKING, FLUSH
D-RINGS: 2 BENT D-RINGS IN TAIL CHANNEL

ADDITIONAL:

PSI TIRE INFLATION SYSTEM
PAINT: BLACK URETHANE WITH 2 PART EPOXY PRIMER
LIQUID FILLED AIR GAUGE WITH CHART
4-WAY PLUG AT REAR
MANUAL RIDE HEIGHT CONTROL

LED LIGHTING
RAISE AND LOWER VALVE
AIR LIFT ON REAR AXLE

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.