



# Hale Trailer Brake & Wheel

## A000145

### 25NTT

25 Ton Tridem Non Tilt

#### Tags

Base Weight: 11,360

#### TRAILER

**Overall Length** 37 ft. 7 in.  
**Overall Width** 102 in.  
**Weight lbs +/- 2%** 12696, including options  
**A-Frame** 6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam  
**Hitch** 3 in. pintle eye, adjustable 5 position 23 1/2 in. to 32 1/2 in.

#### DECK

**Deck Length** 24 ft.  
**Loaded Deck Height** 34 in.  
**Main Frame** Hi-Tensile Wide Flange 14 in. @ 22  
**Cross Members** Hi-Tensile 6 in. Channel @ 8.2  
**Side Rail** Hi-Tensile 8 in. Channel @ 11.5 open on inside  
**Floor** 1 3/8 in. x 7 in. Keruing Shiplapped  
**Landing Gear** Dual 2 Speed

#### SUSPENSION/AXLES

**Axles** 25,000 lbs Capacity 77.5 in. Track 3/4 in. wall 25,000 lbs Capacity 77.5 in. Track 3/4 in. wall, 1 Lift Axle with Control Box c/w Manual Switch in Toolbox, include guard bracket to protect switch.  
**Spread** 49 in.  
**Suspension** Hutch 9700 spring ride., 1 Ridewell RAR 260 Underslung Air ride 25,000lbs. (includes air gauge), bring control box out to the side.  
**Brakes** Quick Change 12 1/4 in. x 7 in.  
**Brake Chamber** #3030, All Axles  
**Air Brake System** 2S/1M  
**Bearings** Oil Bath  
**Slack Adjusters** Automatic  
**Hubs & Drums** 8 Stud Unimount C / W Cast Drums  
**Tires** 235/75R17.5 16 ply  
**Wheels** 6.75 x 17.5 Steel Disc - Painted White

#### BEAVERTAIL

**Length** 6 ft. Beavertail, Planked

#### RAMPS

**Length** \* 38 in. x 76 in. Wood Filled Air Operated Ramp  
**Brackets** \*NPO\*: To hold ramp handle when not in use, 1 per side

#### GENERAL SPECIFICATIONS

**Electrical System** Modular, Vapor Proof GROTE Ultra Blue  
**Lights** LED CMVSS 108 / FMVSS 108  
**Front Connector** SAE J560 7 Pin  
**Finishing** Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked  
**Color** Black  
**Mudflaps** 1 set of BWS at rear  
**Toolbox** Full A Frame mounted with solid bottom and cover

25NTT			
25 Ton Tridem Non Tilt			
Tags			
		Base Weight:	11,360
<b>GENERAL SPECIFICATIONS</b>			
Load Securement	8 pair of D-rings: 7 pain on main deck evenly spaced, 1 pair at headboard on top of main frame		
Fenders	3/16 in. deck plate		
	GVWR Rating is based on standard configuration and a 15% Tongue weight distribution		

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.