



# Hale Trailer Brake & Wheel

## A001797



### RENEGADE XN20 (Model: RENLXT40NF\*832542)

Detailed Specifications		General	
SKU	RENLXT40NF*832542		
Capacity	40 Tons in 16-foot Length - GAWR and GVWR Determine Legal Loads		
Length (Trailer Only)	53 feet 1 inches (closed); 77 feet 0 inches (open)		
Width	8 feet 6 inches		
Compatibility	Designed to Accept Optional Third Flip Axle		
Accent Package	Stainless Steel Bumper Insert		
Weight	Est. Configured Weight: 24305# +/- 3%		
Gooseneck			
Gooseneck Design	Narrow Hydraulic Removable Non-Ground Bearing - Swing Radius of 102 inches (11 feet 11 inches overall Gooseneck Length) Set Up for Wetline Operation		
Loaded Fifth Wheel Height	50-inch Nominal Loaded Fifth Wheel Height with 5 Ride Height Positions		
Power Source	Set Up for Wet Line Operation		
VIN Plate	Bilingual VIN Plate		
Registration/Document Holder	Install Registration/Document Holder		
Deck			
Framework	All Main Longitudinal Members Fabricated with 100,000# Minimum Yield Steel Flanges with 50,000# Webs		
Deck Design	Flat Level Deck Design		
Deck Length	32 feet 0 inches Clear Deck Length (closed) - 56 feet 0 inches (open)		
Loaded Deck Height	20 inches with 6 inches Ground Clearance		
Crossmembers	On 24 inch Centers		
Deck Lock	First 5 Spaced Approx. 12 inches; Others Every 50 inches		
Flooring	1 3/8 inch Nominal Wood (Full Width)		
Recessed Floor Mounted D-Ring Package	None		
Front Ramps	None - Front of Deck Sloped Top Down to Assist in Loading with Traction Cleats		
Extension Brackets	Outriggers - 16 Pair - 32 Total Removable Swing Type, 1 Pair - 2 Total Removable Hook-On Type		
Rear Bridge: General			
Front Bogie Ramp	Sloped Steel Bogie Ramp (Full Width)		
Mini Boom Trough and Traction Cleats	None		
Deck to Bogie Connection	Fixed		
Covered Rear Bogie	Rear Bogie Platform with 1 1/8 inch Wood Floor		
Rear Bogie Height	41 inches		
Connections for Future Axle Attachment	Air and Electrical Connections to Go Along with Connecting Ears		
Rear Bridge: Axles			
Number of Axles	2		
Axle Capacity	25,000 lb. Nominal Capacity Per Axle - NOTE: GAWR Determined By Suspension Type, Brakes, Tires and Other Components		
Axle Spread	54.5 inches (Between Axles)		
Spring Brakes	Spring Brakes (2 Axles)		
Dust Shield	None		
Hubodometer	None		
Rear Bridge: Suspension			
Suspension	Air Ride with Automatic Controls		
ABS	4S/2M System without Diagnostic Tool and Cable		
Chain Lift	None		
Ride Height Control	Automatic/Manual Raise/Lower Control		
Liquid Filled Gauge	Included		
Load Scale	None		

## Detailed Specifications

Wheels and Tires	
Wheels	8.25 x 22.5 Outside LvL one buffed wheels/ Inside Steel Disc - Hub-Piloted
Tires	255/70R 22.5 H Ply OEM Standard
Inflation	None
Lighting	
Electrical System	DOT Sealed Beam and Harness with LED Lights and 4-inch Flush Mounted Battery Powered Amber Strobes
Tail Lights	3 Tail Light Package
Marker Lights	8 Marker Lights Per Side Including Mid-Turn
Special	Not Available on This Model
Electrical Receptacle	J560 7-Pin Connector
Paint	
Paint	Fontaine Black Polyurethane Enamel
Miscellaneous	
Lash Rings	12 Pair - 24 Total
Flag Holders	2 Pair Flag Holders
Additional Options	
Flip Axle	None
Dust Shields on Flip Axle	None
Terms	
Please Note	Price Includes Commodity Surcharges
Commercial Terms	Ex Works- Springville, AL, USA

### RENEGADE XN20



[RENEGADE XN20 Base Model](#) (Note: Options not shown)

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.

