



# Hale Trailer Brake & Wheel A002303



Item <b>LIVE BOTTOM</b>	Description	<b>LBW-241 FALCON TRAILER MOUNT</b>
...BODY CONSTRUCTION:		
CAPACITY	30.5 CUBIC YARDS	
LENGTH	41'	
SIDES	ABRASION RESISTANT STEEL, 1/8" HARD OX STEEL	
INSULATION	COVERED WITH SMOOTH .040 ALUMINUM	
SIDE STIFFENERS	12 GAUGE "J" CHANNELS	
FRAME	TRUSS DESIGN, TUBE FRAME W/WINGS	
CROSSMEMBERS	10 GAUGE	
PRODUCT DOORS	TWIN DOORS WITH INDIVIDUAL AIR CYLINDERS (AIR CONTROL VALVE INCLUDES MANUAL OVERRIDE).	
LIGHTS	L.E.D. TYPE, 12 VOLT SEALED SYSTEM	
PAINT	GLOSS BLACK (2-PART URETHANE)	
FRONT FENDERS	ALUMINUM DIAMOND PLATE	
REAR FENDERS	ALUMINUM DIAMOND PLATE	
...HYDRAULICS AND PRODUCT BELT:		
PLANETARY GEAR	DOUBLE REDUCTION, 31.5:1 RATIO, 130,000 IN. LBS. TORQUE	
HYDRAULIC MOTOR	15.2 C.I.D.	
CONTROL VALVE	NONE	
CHAIN	(8) STEEL PINTLE CHAINS, 12,500 LB. RATED	
LADDER	MOUNTED ON ROADSIDE CENTER W/ FOLDING BOTTOM	
CHAIN ADJUSTMENT	INDEPENDENT TENSIONING MECHANISM	
CHAIN GUIDANCE SYSTEM	ULTRA-HIGH MOLECULAR POLYETHELENE TO REDUCE FRICTION AND WEAR	
PRODUCT BELT	42" WIDE, CHEMICAL AND HEAT RESISTANT, CONTINUOUS-NO SLATS	
BELT ADJUSTMENT	INDEPENDENT ADJUSTMENT AND TENSIONING MECHANISM	
BELT RETAINER	"V" STYLE BELT CENTERING FOR POSITIVE ALIGNMENT	
...CHASSIS:		
LANDING GEAR	TELESCOPIC PIN TYPE	
SUSPENSION	23,000# AIR RIDE TANDEM	
AXLES	(2) 23,000 LB. BEAM RATING	
AIR BRAKES	16.5" X 7" W/SPRING BRAKE AND AUTO SLACK ADJUSTERS	
OIL SEALS	STEMCO	
HUBS	10-STUD, HUB PILOTED STEEL	
DRUMS	CAST	
WHEELS	10-HOLE, HUB PILOTED STEEL, PAINTED WHITE	
TIRES	(8) 11R22.5-G	
...MISCELLANEOUS:		
TARP	SHURCO ELECTRIC FRONT TO REAR W/ MANUAL OVERRIDE	
STROBE LIGHTS	AT REAR (SET OF 2)	
WORK LIGHTS	AT REAR (SET OF 2)	
HYDRAULIC JUMPER HOSES W/SPRING SUPPORT	TRAILER TO TRACTOR	
BACKUP ALARM	ELECTRIC	

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.