

# HALE

## TRAILER

### BRAKE & WHEEL

## Hale Trailer Brake & Wheel A002313

### X-L SPECIALIZED TRAILERS, INC.

OAL: 58' 9"  
OAW: 102"

MODEL: XL 140HDE

DIST: 140,000#

CONC.

120,000# IN 10' CLOSED

WEIGHT +/-3%

#### GOOSENECK-

LENGTH: 13' 8" NARROW  
KING PIN SETTING: 16"  
SWING CLEARANCE: 113"  
5TH WHEEL HEIGHT: 52" W/ 6 VARIABLE RIDE HEIGHT POSITIONS  
HYDRAULICS: 13 HP HONDA UNIT SET UP WITH DUAL HYDRAULICS  
TOOLBOX IN REAR OF GOOSENECK WITH CHAIN RACK, ALUMINUM LID  
LIGHTS: ( 2 ) WORK LIGHTS MOUNTED IN REAR BASE NECK WITH SWITCH  
FLIP NECK: FRAME REINFORCEMENT, AIR, ELECTRIC AND BRACKETS FOR 9' 9" FLIP NECK EXT.  
HYDRAULIC ASSIST FLIP NECK  
FLIP NECK: 9' 9" FLIP NECK EXTENSION - GIVES 230" OF SWING CLEARANCE

#### MAIN DECK-

LENGTH: 29' / OPENING TO 50' 3"  
LOADED DECK HGT: 26" W/ 6" GROUND CLEARANCE  
DECKING: 1 3/8" APITONG DECKING, RAISED, CENTER COVERED UNDER BELLY PIN  
CROSSMEMBER: 6" JR. I-BEAM ON 12" ALTERNATING CENTERS  
SIDE BEAMS: FAB I-BEAM  
D-RINGS: 13 BENT D-RINGS PER SIDE TOTAL OF 26  
OUTRIGGERS: REMOVABLE SWING OUT OUTRIGGERS - 24" O/C  
REINFORCEMENT: TOP FLANGE REINFORCEMENT  
CHAIN DROPS: ( 10 ) CHAIN DROPS PER SIDE - OUTSIDE BEAMS ONLY

#### REAR DECK:

LENGTH: 16' 1"  
LOADED DECK HEIGHT: 38"  
AXLES: ( 3 ) 25,000 NOMINAL, 80 3/4" TRACKING, STEERABLE AXLES  
SUSPENSION: RIDEWELL / 25,000 AIR  
AXLE SPACING: 60"  
ABS: N/A WITH SPRING BRAKES ON 1 AXLE  
TIRES: MICHELIN 245/70R/17.5  
WHEELS: 6.75 X 17.5 STEEL INSIDE, ALUMINUM POLISHED OUT DISC WHEELS  
BRAKES: 12 1/4" X 7 1/2"  
DRUMS: HUB PILOT/ OUTBOARD DRUMS  
ELECTRICAL: 12V SEALED GROTE SYSTEM WITH 3 TAILLIGHT ALUMINUM PACKAGE  
DECKING: OPEN WHEELS, BOLSTER STYLE WITH CENTER COVERED WITH RAISED 1 3/8" APITONG  
D-RINGS: 2 BENT D-RINGS IN TAIL CHANNEL  
2 BENT D-RINGS ON EACH BOLSTER

#### ADDITIONAL:

PAINT: GREASE HUBS IN LIEU OF OIL  
BLACK  
ONE PAIR OF FLAG HOLDERS IN REAR  
RAISE AND LOWER VALVE MOUNTED BETWEEN AXLES - ROADSIDE  
31" FRONT LOADING RAMPS  
FRAME REINFORCEMENT, AIR, BRACKETS, ELECTRICAL FOR 3 AXLE POWER BOOSTER  
SET UP TO FIT VIN 18723 (FOR 130SDE)  
4" AMBER STROBE LIGHT TO BE USED AS 3RD TAIL LIGHT WITH BATTERY BACK UP  
PSI TIRE INFLATION SYSTEM  
AIR WEIGH DIGITAL SCALE (QUICKLOAD)  
2 ADDITIONAL CLEARANCE LIGHTS PER SIDE ON MAIN DECK - EVENLY SPACED  
LED LIGHTING - STANDARD  
DETACHABLE WHEEL AREA WITH HORIZONTAL MANUAL PINS  
( 2 ) TOTAL MID TURN LIGHTS PER SIDE  
4-WAY PLUG AT REAR FOR BATTERY BACKUP  
EXTENSION STOPS 24" O/C  
(2) 6 FUNCTION WIRELESS REMOTE FOR STEERING THE AXLES AND BUMP STEERING THE POWER BOOSTER

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.