



Hale Trailer Brake & Wheel

A003328

X-L SPECIALIZED TRAILERS

OAL: 53'
OAW: 102"

MODEL: XL 90HDE DIST: 90,000# CONC. 70,000# IN 10' CLOSED WEIGHT +/-3% 0

GOOSENECK-

LENGTH: 10' 5" NARROW NECK
KING PIN SETTING: 16"
SWING CLEARANCE: 84"
5TH WHEEL HEIGHT: 49" W/ 7 VARIABLE RIDE HEIGHT POSITIONS
HYDRAULICS: RUN OFF WET LINE
FLIP NECK: FRAME REINFORCEMENT, AIR, ELECTRIC AND BRACKETS FOR 36" FLIP NECK EXTENSION
36" FLIP NECK EXTENSION

MAIN DECK-

LENGTH: 33' 7" / OPENING TO 59' 11" - 30" MINI DECK
LOADED DECK HGT: 20" W/ 6" GROUND CLEARANCE
DECKING: 1 1/8" APITONG DECKING, FLUSH, CENTER COVERED
CROSSMEMBER: 6" JR. I-BEAMS ON 12" ALTERNATING CENTERS
SIDE BEAMS: FABRICATED OUTSIDE RAIL
D-RINGS: 8 BENT D-RINGS PER SIDE
CHAIN DROPS: CHAIN DROPS ON 24" CENTERS
OUTRIGGERS: REMOVABLE SWINGOUT OUTRIGGER BRACKETS ONLY ON 24" CENTERS
DOUBLE FRONT OUTRIGGER BRACKETS ONLY AT FRONT
RAMPS: TAPERS TO 4"

REAR DECK:

LENGTH: 9'
LOADED DECK HEIGHT: 40"
AXLES: (2) 25,000 NOMINAL, 77 1/2" TRACKING
SUSPENSION: HEND-TURNER/25,000 AIR
AXLE SPACING: 54"
ABS: 4S2M SPRING BRAKES ON 2 AXLES
TIRES: 255 / 70R / 22.5
WHEELS: 8.25 X 22.5 STEEL INSIDE, ALUMINUM POLISHED OUTSIDE DISC WHEELS
BRAKES: 16 1/2" X 7"
DRUMS: HUB PILOT/ OUTBOARD DRUMS
ELECTRICAL: 12V SEALED GROTE SYSTEM WITH 3 TAILLIGHT ALUMINUM PACKAGE
4" AMBER STROBE WITH SWITCH TO MAKE 3 STT
DECKING: 1 1/8" APITONG DECKING FLUSH, COVERED WHEELS
D-RINGS: 2 PAIR OF PAN STYLE D-RINGS - ONE IN EACH CORNER
2 STAKE POCKETS IN TAIL CHANNEL

ADDITIONAL:

PAINT: BLACK URETHANE WITH 2 PART EPOXY PRIMER
2 PAIR OF FLAG HOLDERS
MANUAL RIDE HEIGHT CONTROL
FRAME REINFORCEMENT, AIR, ELECTRIC AND BRACKETS FOR 2 AXLE BOOSTER
RAISE AND LOWER VALVE
EXTENSION STOPS ON 24" CENTERS

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.