





Resale Inventory
A004729
VIN: 137288

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Jacksonville, FL: 800-828-3055
Baltimore, MD: 888-601-7500	Little Rock, AR: 833-424-8944
Boston, MA: 800-854-5310	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Richmond, VA: 866-839-3495
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE	TELESCOPIC SEMI-TRAILER, STEEL PLATFORM. 
DIMENSIONS LENGTH LENGTH OPENINGS WIDTH HEIGHT	48'-0" closed. 80'-0" opened. 5'-0" increments in closed position. 102", 97" between side rails. Floor, approximately 61 1/4" high at front and 58" at rear.
COUPLING COUPLER PLATE KING PIN LOCATION COUPLER HEIGHT	5/16", plug welded structure. 24" from front. 49".
STRUCTURE FLANGES FLANGES WEB GOOSENECK CROSSMEMBERS FLOOR FLOOR FASTENING SIDE RAILS SIDE BOXES RUB RAILS CORNERS DIAGONAL BRACES X BRACES LOCKS ROLLERS	Frame with "CAMBER". Female section, exterior, 3/8" x 6", 100 000 psi steel, 24" high. Male section (interior), 1/2" x 6", 100 000 psi steel, 17 5/8" high. (For tandem suspension Only) 1/4" plate in king pin area and the remaining in 3/16", 80 000 psi steel. 12" high, with integrated nose ramp and 48" straight behind king pin. 1 beams, 4" @ 3.64 lbs/ft, 80 000 psi steel, 12" centre to centre. Aptong, 1 1/8" thick shiplap finished, no preservative. Two screws per board at each crossmember. 6" channel @ 8.2 lbs/ft. 3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high. (USA Dimensions). 3/8" x 2 1/2" shaped steel. Bevelled. 2" x 2" x 3/16" angles, welded in web and to a crossmember, located each side. Between main beams, full length. Air operated with a third glad hand at front. 4, 2 on female sections of frames and 2 on male sections.
ENDS FRONT RAIL BUMPER HEADBOARD POCKETS REAR RAIL	9 gauge formed steel. CMVSS 223-RIG approved (in accordance with Canada & USA regulations). Uprights integrated with frames, 4" x 4" cross bar roll formed tubing at a maximum height of 22" from under tubing to ground. 48" high, steel, 4 uprights and top made of tubing and 11 gauge steel plate installed inside with retroreflective tapes. 2 welded pockets at front for removable headboard. 11" high, 9 gauge formed steel, including 3 boxes at rear and 3/8" x 2 1/2" shaped steel.
ELECTRICAL FRONT CONNECTOR ELECTRICAL SYSTEM MAIN SYSTEM	7 way (SAE J560), Phillips brand. Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108. Grote Ultra Blue LED, grounded to front connector, sealed beams Grote.



ITEM	DESCRIPTION
TURN SIGNAL	(tail lights with male pins #54332, markers #47122, 47233 (2 1/2" dia.), licence light #60280-M, with vapor proof junction box Truck-Lite #50400). Sealed beams LED, (Grote #54163), one lamp including side marker and flasher, each side at middle point, amber.
LANDING GEAR SAND SHOES CRANK	Holland, Mark V (LGS-4F115). 10" x 11 1/2". Road side.
BOGIE SUSPENSION U-BOLTS SPRINGS AXLE(S) SPIDERS CAM SHAFTS TRACK DUST SHIELDS BRAKES BEARINGS SLACK ADJUSTERS SEALS BRAKE CHAMBERS HUBS AND DRUMS RIMS TIRES TIRES MANUAL STOP BAR	Slider, Hutch H-9801, "UHMV" slider plastic pads, 4 locking pins, For 49" spread tandem spring suspension. 4" c/c between locating holes, (48" travel). Hutch H-9700, tandem, underslung, under mount, 49" spread. With nuts at bottom. 3 leaves, model TRA 2740 or 365-00, 12 000 lbs capacity. Meritor, TQ 4671, 25 000 lbs. capacity. (982-1058, supplier couldn't supply 1/2"). Welded. 28 splines with bolt-on bushing. 77 1/2". Steel, bolted. 16 1/2" standard, FRAS-LE MA212Q+ extended life lining. HM 218248 and HM 212049. Meritor, automatic, 28 splines. Stemco, "Platinum Performance System". Including "Guardian" seals, Pro-Torq spindle nuts, Integrated sentinel hub caps with Synthetic oil, Mobil Delvac 75W-90. (3 year warranty by Stemco for parts only). T.S.E. brake, "Omnibrake" (30-30). 10 studs disc hubs, outboard mount, 285.75mm B.C., single flange nuts. For dual steel wheels or single steel or aluminium wheels. 22.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts, 2 hand holes. Continental, 275/80 R 22.5 HTL ECO-PLUS 14 ply (39.7") NOTE: "Tires on imports do not qualify for a Fair Market Value Deduct toward F.E.T. calculation". One, Hutch.
AIR SYSTEM GLAD HANDS AIR VALVES VALVE DIAGNOSTIC CABLE	Fixed. Rockwell Wabco, ABS, 2 sensors 1 modulator. Fast-brake kit. not included with ABS valve.
ACCESSORIES REGISTRATION HOLDER WINCHES SLIDING TRACK	One plastic, Betts-PS-1 or equivalent. Qty: 12, #1020ZP, zinc plated slider (5"). Full length, "LL" extruded aluminum, road side.



ITEM	DESCRIPTION
MUD FLAPS	One set, rubber with Manac logo and vertical grooves to reduce spray.
FINISHING PAINT	Shot blasted, one coat of epoxy primer and two acrylic urethane top coats, Color: black, code: U-TECH RM 99U.
HUBS	Same color as trailer.
WHEELS OR RIMS	White.
RETROREFLECTIVE TAPES	Conspicuity striping in compliance with CMVSS 108. Gray and red each side, fully covers rear sill and horizontal underride protection bar.
PAINTED AXLES	Same color as trailer.

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.