



Hale Trailer Brake & Wheel

A006029
VIN: 34961

Base Model: DC48x102 Air Spread

Serial #: 34961

components description

CAPACITY Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)

OVERALL LENGTH 48' - Base Weight 10,640#

UPPER DECK LENGTH 10'

LOWER DECK LENGTH 38'

OVERALL WIDTH 8' 6"

KING PIN SETTING 18" - Squared Front

UPPER COUPLER PLATE 1/4"

UPPER COUPLER HEIGHT 48"

FRONT SKIRT Aluminum Front and Corners

REAR SKIRT Aluminum

BULKHEAD None

MAIN FRAME 26" Fab.-PreCamb.I-Beams-(80K Pkg)

SIDE RAILS 6"-Alum-Extruded W/Double L Track

TOP DECK FLOOR SILLS 4" Steel I-Beam - 18" O.C.

LOWER DECK FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg

COIL HAUL PACKAGE Single Coil Placement - 5 Extra Stud Sills-Ctr On Trailer

FLOOR DECKING 1-1/8" HD Aluminum W/4 Nailer Boards

WINCHES 12 DOUBLE L (+)#75

WINCH TRACK Double L Aluminum - Extruded Siderail R/S Only

TIE BAR Curb Side - Full Length - 3/8" x 2"

STRAPS None

LANDING GEAR Two Speed - Jost A500

SUSPENSIONS Air Ride - Hendrickson Intraax - 23K - 2 Axles

SUSPENSION LOCATION Set at Rear most Position - 32.5" Center of Rear Axle to Rear of Trailer

AXLES (2) 22.5K Cap.- Type 30 Chambers - Auto Slacks - ABS - 22.5 Tires (1463#)

AXLE SPACING 10'2" Wide Spread

LIFT AXLE None

DUMP VALVE Elect.-Wired Thru Aux 7way Plug @ Front of Trailer-Dump Rear Axle(+9#)

SCALES None

PARKING BRAKES All Axles

ABS SYSTEM Wabco ABS System 2S/1M

DUST SHEILDS None

WHEELS Disc - Hub Piloted - 22.5 - Steel Inner and Durabrite Outer

Durabrite Outer Wheels.

TIRES 255/70R 22.5 - 41" Loaded Deck Height - Double Coin

TIRE INFLATION SYSTEM None

ANTI-SAIL MUD FLAPS Behind All Axles

STAKE POCKETS 24" O.C. Sides & 5 Across Rear

SPOOL Triangular Shaped

RUB BAND ALUM 3/8" x 3" - Aluminum - Recessed for DOT Tape

DOCK BUMPERS Rubber Inboard

CARGO TIE DOWN 14 Pair of Recessed Chain Ties Evenly Spaced

CONTAINER TWIST LOCKS None

TIRE CARRIERS Tire Carrier Positioned In Front of Main Beams Between Landing Gear

DUNNAGE RACK None

TOOLBOX MATERIAL None

TOOLBOX TYPE None

TOOLBOX LOCATION None

LIGHTS Grote Ultra Blue Sealed Wiring Harness- 2 Micros Per Side & Mid Turn-3/3/3 Rear

CUSTOM LIGHTS 6 Total Marker Lights Per Side

PAINT Black - PPG Epoxy Primer and Acrylic Polyurethane - Shot Blasted

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.