



## Hale Trailer Brake & Wheel

A007065

VIN: 21334

### XL 80 Mechanical Full-Width Gooseneck

OVERALL LENGTH 53'  
OVERALL WIDTH 102"  
CAPACITY 80,000 LB DISTRIBUTED; 70,000 LB IN 16'  
WEIGHT +/- 3% 0,000 LB

#### GOOSENECK

LENGTH 10'  
KINGPIN SETTING 16"  
SWING CLEARANCE 84"  
5TH WHEEL HEIGHT 49"  
DECKING 1 1/8" APITONG DECKING FLUSH  
ALUMINUM MUDFLAPS  
TOOL BOX TOOL BOX ON BASE OF NECK WITH ALUMINUM LOCKABLE LID - RACK AND WORK LIGHT

#### MAIN DECK

LENGTH 34'  
LOADED DECK HEIGHT 18" W 6" GROUND CLEARANCE  
DECKING 1 1/8" APITONG DECKING, FLUSH  
CROSSMEMBER 6" & 4" JR I-BEAM ON 12" ALTERNATING CENTERS  
SIDE BEAMS 4 FAB I-BEAMS 12"  
D-RINGS 8 BENT D-RINGS PER SIDE- 16 TOTAL  
4 PAN STYLE D-RINGS PER SIDE  
OUTRIGGERS SWINGOUT OUTRIGGERS ON 24" CENTERS  
RAMPS TAPERS TO 4"  
CHAIN DROPS (14) CHAIN DROPS PER SIDE - OUTSIDE BEAMS

#### REAR DECK

LENGTH 9'  
LOADED DECK HEIGHT 41"  
AXLES ( 2 ) 25,000 NOMINAL, 77 1/2" TRACKING  
SUSPENSION HENDRICKSEN - TURNER / 25,000 AIR  
AXLE SPACING 54"  
ABS 4S2M WITH SPRING BRAKES ON 2 AXLES  
TIRES 275 / 70R / 22.5  
WHEELS 8.25 X 22.5 STEEL INSIDE, ALUMINUM POLISHED OUTSIDE DISC WHEELS  
BRAKES 16 1/2" X 7"  
DRUMS OUTBOARD  
ELECTRICAL 12V SEALED GROTE SYSTEM WITH 2 TAIL LIGHT ALUMINUM PACKAGE  
DECKING 1 1/8" APITONG DECKING, FLUSH  
D-RINGS ONE PAN STYLE IN EACH CORNER  
2 STAKE POCKET IN TAIL CHANNEL

#### PAINT

BLACK

#### ADDITIONAL

NO RAISE AND LOWER VALVE  
FRAME REINFORCEMENT, AIR, BRACKETS, ELECTRICAL FOR FLIP AXLE  
TRIPLE DONUTS  
MANUAL RIDE HEIGHT CONTROL  
(5) TOTAL LIGHTS PER SIDE - LED  
DUST SHIELDS  
1/4 TURN DUMP VALVE  
( 1 ) 4 WAY PLUG AT REAR OF TRAILER  
STROBE POLE MOUNT IN WHEEL AREA WITH PIN - TO ACCEPT 1 1/4" SQUARE TUBE IN CENTER  
OF THE REAR LIGHT PANEL  
LIQUID FILLED AIR GAUGE WITH CHART  
2' CUTOUT IN REAR TRANSITION AREA  
2 PAIR OF PULLOUT LIGHTS, 1 AT FRONT AND 1 AT REAR

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.