



Hale Trailer Brake & Wheel
A007602
VIN: 001392



42ET2X	
42 ft. Tandem	
Equipment	
	Base Weight: 12,100
TRAILER	<p>Overall Length 42 ft.</p> <p>Overall Width 102 in.</p> <p>Weight lbs +/- 2% 13633, including options</p>
GOOSENECK	<p>Coupler Weld in King Pin</p> <p>Coupler Plate 5/16 in. Hi-Tensile, 48 in. Height</p> <p>Coupler Location 18 in.</p> <p>Length 10 ft. 6 in.</p> <p>Cross Members Hi-Tensile 4 in. Jr. I-beam @ 16 in. O/C</p> <p>Swing Clearance 83 in.</p> <p>Floor *NPO*: 1 1/2" All Keruing Floor</p> <p>Web 1/4 in. Hi-Tensile</p> <p>Roller Stop *NPO*: 6 in. X 4 in. X 1/4 in. Tubing full width of GNK. Stitch weld to GNK flanges & front skirt.</p>
DECK	<p>Deck Length 25 ft. 1 in.</p> <p>Loaded Deck Height 35 in.</p> <p>Main Frame 3/8 in. x 5 in. Top and Bottom Flanges 100 KSI</p> <p>Cross Members Hi-Tensile Standard 4 in. I-beam @ 12 in. O/C on Lower Deck w/ Knee Braces</p> <p>Side Rail 6 in. @ 8.2 Channel</p> <p>Web 3/16 in. Hi-Tensile</p> <p>Floor *NPO*: 1 1/2" All Keruing Floor</p> <p>Landing Gear Dual 2 Speed</p> <p>Load Securement * Moulded Rub Rail, Stake Pockets and Spools 24 in. OC</p> <p>Load Securement 9, Pair of in Floor Flush Mounted D-Rings: 3pr. GNK, 2pr. B/T, 4 pr. Main deck starting directly after front ramp, evenly spaced</p>
SUSPENSION/AXLES	<p>Axles 25,000 lbs Capacity</p> <p>Spread 49 in.</p> <p>Suspension Ridewell RAR 260 U/S 6 1/2 in. Air Ride 25,000 lbs - includes air gauge and dump valve in enclosure</p> <p>Brakes Quick Change 12 1/4 in. x 7 in.</p> <p>Brake Chamber #3030, All Axles</p> <p>Air Brake System 2S/1M</p> <p>Camshafts 28 Spline Non Enclosed</p> <p>Slack Adjusters Automatic</p> <p>Hubs & Drums 8 Stud Unimount C / W Cast Drums</p> <p>Tires Tire Upgrade to 245/70R17.5 Continental HTL2 ECO</p> <p>Wheels 6.75 x 17.5 Steel Disc - Painted White</p>
BEAVERTAIL	<p>Length 5 ft. @ 8 degree slope, Planked</p>

42ET2X

42 ft. Tandem

Equipment

Base Weight: 12,100

RAMPS

Rear * 38 in. x 76 in. Air Operated Planked In

Front * 5 ft. Inset Full Width Air Operated (Inset in Floor to Access Upper Deck)

GENERAL SPECIFICATIONS

Electrical System Modular, Vapor Proof GROTE Ultra Blue

Front Connector SAE J560 7 Pin

Rear Connector 4 Pin Plug

Lights *NPO*: City Light package in the ramps BUT also keeping lights in bumper

Finishing Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked

Color Black

Mudflaps 1 set of BWS at rear

Fenders 3/16 in. Formed Deck Plate

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.