

			OAL: 53' OAW: 102"
MODEL: XL 90 BM	DIST: 85,000# CLOSED	CONC.	
VIN#: 4U3B05334ML0	020449		WEIGHT+/-3%=
GOOSENECK-			
LENGTH:	9'		
KING PIN SETTING:	19"		
SWING CLEARANCE: 5TH WHEEL HEIGHT:	77" 49"		
LANDING GEAR:	2 SPEED LANDING GEAR - HANDLE	E ON CURSIDE	TRAILERS TM
	DROP LEGS FOR PARKING LOADEI	O TRAILER	
FENDERS:	BOLT ON ALUMINUM FRONT FENDI	ERS	
D-RINGS:	(2) D-RINGS ON FRONT		
	(2) D-RINGS PER SIDE - 4 TOTAL		
	(4) D-RINGS ON REAR OF GOOSEN	ECK	
PLATFORM:	48" LOADING PLATFORM ON FRON	т	
DECK HEIGHT:	57" DECK HEIGHT ON PLATFORM		
MAIN DECK-			
LENGTH:	OPENS TO 184' 2" WITH PULLOUT E	BUMPER	
LOADED DECK HGT:	51"		
PLATFORM:	18" STEEL PLATFORM AT REAR W/ 4 D-RINGS		
MAIN FRAME:	TELESCOPING MAIN FRAME (4 TO	TAL SECTIONS)	
FLAG HOLDERS:	(3) PAIR OF FLAG HOLDERS 20' PULLOUT BUMPER WITH STOPS ON 24" CENTERS - NON LOAD BEARING BUMPER		
BUMPER: D-RINGS:	(1) PAIR IN TAIL CHANNEL		
REAR DECK:			
AXLES:	(3) 25,000 NOMINAL, 80" TRACKING	3	
SUSPENSION:	HEND-TURNER / 25,000 AIR		
AXLE SPACING:	71"		
ABS: TIRES:	2S1M SPRING BRAKES ON 1 AXLES 245/70R/17.5	5	
WHEELS:	6.75 X 17.5 STEEL DISC WHEELS		
BRAKES:	12 1/4" X 7 1/2"		
DRUMS:	HUB PILOT/ OUTBOARD DRUMS		
ELECTRICAL:	12V SEALED GROTE SYSTEM WITH	I 3 TAILLIGHT PACKAGE	
MUD FLAPS:	MINIMIZER WHEEL COVER OVER E	ACH AXLE WITH MUDFLA	۱P
ADDITIONAL:	RAISE AND LOWER VALVE		
PAINT:	BLACK URETHANE WITH 2 PART E	POXY PRIMER	
	LIQUID FILLED AIR GAUGE		
	13HP HYDRAULIC POWER UNIT		
	LODAR REMOTE FOR STEERING		
	4" AMBER STROBE LIGHT TO BE US	SED AS 3RD TAIL LIGHT	
	(2) BUNK SECTIONS		
	(1) 48" ROLLING SECTION WITH	55" HEIGHT OVER REAR I	MOST BEAM ONLY
	PSI TIRE INFLATION SYSTEM		

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.