

## TK110SA 3 axle Sliding Axle trailer; 110,000 lbs uniform / 70,000 17334-110SA

## 17334-Base

			Weight	
Item #	Category	Description	(lbs)	Qty
17334	Open Deck	TK110SA 3 axle Sliding Axle trailer; 110,000 lbs uniform / 70,000 lbs in 10 ft.		
17338	Overall Length	52'-11" overall length		
17339	Overall Width	102" wide		
17233	Fifth Wheel / King Pin	49" loaded 5th wheel height		
17238	Upper Deck	48" Headboard (removable) w/ provisions for bolt on lockable chain storage rack and chain basket		
17240	Upper Deck	2 side access tool boxes at front of upper deck		
17345	Upper Deck	9'0" Straight drop upper deck (14" kingpin setting with 86" swing clearance)		
18517	Upper deck	Tilting main deck - forms a ramp to uper deck		
O9998	Winch	Alternative Option Selected. See Add'l Options Section Below.		
17253	Winch	Delete Winch guard	(61)	
17255	Winch	Winch roller (Recessed at rear of upper deck)	29	
17257	Hydraulics / Controls	PTO hydraulics		
17261	Hydraulics / Controls	Push - Pull style hydraulic valve controls w/ full- function wireless remote controls (Dual side controls)		
17262	Landing Gear	2-speed park stands (crank road side)		
17370	Main Deck	Triangle cutouts		
17373	Main Deck	3" crossmembers on 8" centers		
17374	Main Deck	Approximately 7 degree load angle / 15 degree dump angle (17.5 tires & 48' OAL trailer)		

17375	Decking, Main Deck	1 3/8" (NET) apitong deck raised			
17380	Decking, Approach Plate	3/8" smooth approach plate with 4-way slots on approach plate			
17383	Tie Downs	Internal 2-way key slots on approximately 24" centers length of trailer in inner and outer beams			
14672	Suspensions / Axles	Air ride suspension			
17391	Suspensions / Axles	Air Ride raise & lowering control panel on upper deck with liquid filled guage			
17392	Suspensions / Axles	25,000 lb. capacity axles		3	
18518	Suspensions / Axles	No traveling hydraulic lines for sliding axle operation			
17401	Axle Spacing	50" Axle Spacing			
17404	Brakes	12.25 X 7.5 Drum brakes (For 37.5" deck height, select 17.5 wheels and tires)			
17405	Brakes	4S2M ABS Brakes			
14138	Hub / Drum	Steel hub-piloted - cast drum (per complete axle)		3	
08182	Wheels (inside)	6.75 x 17.5 8-hole steel disc wheel		6	
15004	Wheels (outside)	6.75 x 17.5 8-hole polished (XP) aluminum wheel (per wheel) ILO Std 6.75 x 17.5 8-hole steel disc wheel	(144)	6	
10058	Spare Wheel	No Spare Wheel			
18000	Tires	Continental 245/70R17.5 HTL2 - 18 ply		12	
10059	Spare Tires	No spare tire			
14759	Flaps, Mud Guards & Fenders	Mudflaps			
17413	Lights / Electrical	Grote Electrical system (meets DOT regulations)			
17414	Lights / Electrical	Single Mid-turn signal w/ clearance lights X-O-X (whole trailer)			
17416	Lights / Electrical	3rd tail light package			
18233	Lights / Electrical	No front swingout light			
18235	Lights / Electrical	No rear swingout light			
17327	Flagholders	Flag Holders at rear of trailer			
17424	Miscellaneous	Central located lube system			
08024	Paint	S7203 Black with white decals			
17866	Paint	Zinc-rich primer			
18508	Paint	Red & White conspicuity markings			

## 17334-Additional Options

		·	Weight	
Item #	Category	Description	(lbs)	Qty
17250	Custom Options	30,000 lb. hydraulic winch with level wind (mounted above king pin) Includes 5/8" x 80' cable 17253		
17331	Miscellaneous	Fold-down step and handle road side		
17332	Miscellaneous	Fold-down step and handle curb side		
14160	Wheels, Miscellaneous	PSI Tire Inflation System (3 Axle)		
17876	Upper Deck	Bolt on lockable chain storage rack with chain basket (requires option 17238)		
17419	Lights / Electrical	Recessed LED light bar in GN drop with single switch on the driver's side		
17330	Miscellaneous	Air Weigh system (per Advantage HT axle group) - read-out located on GN near hydraulic controls		
201458	Custom Options	Custom Option 201458 SA/HT- Light bar, bulkhead mounted includes stop/tail/turn lights. Used with 4' headboard option)		

DISCLAIMER