

A011018 VIN: 111287

Series: HYDRAULIC DETACHABLE GOOSENECK

Model: RTN55TD3

Item	Description
MODEL	RTN55TD3
TONS CAPACITY	55 TONS IN ANY 12'
CONSTRUCTION	(4) I-BEAM, CAMBERED, T-1 STEEL
PLATFORM WIDTH	8'-6"
PLATFORM LENGTH	26' (OVERALL LENGTH MUST BE 53'-0" OR LESS AND MUST HAVE 43'- 0" OR LESS FROM THE 90" SWING TO THE CENTER OF MIDDLE AXLE).
PLATFORM HEIGHT/ROAD CLEARANCE	18"/6" (12" DEEP MAIN BEAMS)
CROSSMEMBER SPACING	ON 20" CENTERS
FRONT FOLDING RAMPS	STEEL WITH TRACTION BARS
FRAME REINFORCEMENT	FOR A 3+1 (14'-1" SPREAD)
TOP FLANGE REINFORCEMENT	OUTSIDE OF OUTER BEAMS ONLY
BUCKET TROUGH	LAST 3 CROSSMEMBERS OF DECK
HYDRAULIC SYSTEM	FROM TRACTOR WETLINE
GOOSENECK (NEW DESIGN)	NON-GROUND ENGAGING REMOVABLE-HI LIFT
GOOSENECK SUPPORT CYLINDER	HYDRAULIC
GOOSENECK CONNECTION	PIN & STIRRUP TYPE W/ VERTICAL AIR LOCK PIN
SWING CLEARANCE	108" & 90"
FIFTH WHEEL HEIGHT	48"-50"-52"-54"-56" LOADED (ADJUSTABLE)
1/8" ALUMINUM TOP COVER	OVER GOOSENECK AREA
AIR BRAKES	16.5" X 7" W/ AUTO SLACKS & OUTBOARD DRUMS
ANTI-LOCK BRAKES	NONE (TRAILER GVWR EXCEEDS 120,000#)
SPRING BRAKES	ON ONE AXLE
AXLES	(3) 25,000# 3/4" WALL W/23,000# BRAKES
TIRES	(12) 275/70R22.5 (H)
WHEELS	ACCUSHIELD OUTERS, STEEL DISC INNERS, WHEEL COVERS
SUSPENSION	AIR RIDE W/ 52" AXLE SPACING
SUSPENSION	AIR LIFT 3RD AXLE ONLY
SUSPENSION	+3/-3 HEIGHT CONTROL, AUTO/MANUAL
MANUAL EXHAUST VALVE	ON ALL AXLES
LIGHTS	L.E.D. TRUCK-LITE RUBBER SEALED SYSTEM
AMBER L.E.D. STROBES	IN 3RD TAIL LIGHT POSITION WITH SWITCH
BATTERY BACK-UP	AMBER STROBE LIGHTS ON BATTERY BACK-UP
LASH RINGS	(18) TOTAL, 6-PER SIDE, BENT STYLE, 1-EACH SIDE FRONT OF DECK FLAT STYLE ON 45 DEGREE ANGLE, 1-EACH BOLSTER END FLAT STYLE
EXTENSION BRACKETS (OUTRIGGERS)	12" SWING/REMOVABLE W/ DBL HOOK-ON FRONT
DECKING	1-1/2" APITONG (OUTSIDE MAIN BEAMS ONLY)
PAINT	GLOSS BLACK (2-PART URETHANE) STEEL PARTS TO MATCH PAINT COLOR
BOOMWELL	OPEN BOTTOM W/EXTRA LOW 1ST CROSSMEMBER (NO COVER PLATE)



TRACTION BARS	ON FRONT & REAR SLOPES
CHAIN HOOKS & FLAG HOLDER SLOTS	ON BOLSTERS
FLAG HOLDER W/ THUMB SCREWS	1-PAIR FRONT CORNER OF DECK, 1-PAIR ENDS OF LIGHT PANEL
ALUMINUM STORAGE BASKETS BOLT-IN	(1) 2ND SECTION FROM FRONT OF DECK
AIR AND ELECTRICAL CONNECTIONS	FOR FUTURE FLIP/REMOVABLE AXLE

Etnyre reserves the right to modify pricing on all quotes and orders with material and labor surcharges as needed