

# HALE TRAILER BRAKE & WHEEL



Resale Inventory  
A011338  
VIN: 31425

## SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

## TKIIOHDG Advantage Plus Hydraulic Detachable

### 10003 - STANDARD EQUIPMENT

110,000 lbs. concentrated in 12'  
Frame reinforced for single axle booster or flip axle  
16" Kingpin setting/ 50" loaded 5th wheel height -5-position  
gooseneck height adjustment +/- 4"  
Gooseneck arched for increased truck fender clearance  
Hydraulic self-lifting detachable gooseneck  
(can lift above or below transport positions)  
Hydraulic gooseneck support arm  
Air-activated, positive self-locking pin on gooseneck Gooseneck  
doesn't require ground bearing pads  
31" front loading ramps (1 pair)  
4-beam main frame construction  
1-3/4" Apitong decking (raised)  
10" I beam crossmembers on 24" centers  
4" stub crossmembers for 12" centers in outer bays  
Swing-out outriggers with planks  
Pullout HD outrigger at front, double swing-outs at center  
Knuckle trough at rear of deck. 72" long, covered with 1/4" steel  
3rd axle air lift  
Full depth boom trough in wheel area  
Boom trough covered with 10ga. steel  
Mud Flaps

Flag holders front of deck and rear of trailer  
Wide load sign brackets  
Triangle cut-outs on deck beams and bolster  
14 bent-style D-rings on deck, 2 D-rings on wheel area  
Brackets, air and electrical for single axle booster/flip  
Rubber mounted sealed lights and harness system  
LED light package (50-state legal)  
3 Tail lights per side (amber in center)  
Electrical system per DOT regulations  
Air, electrical, and hydraulics installed after paint  
7-pole electrical connector  
Air ride suspension  
Adjustable ride height  
Raising/lowering air control panel  
16 1/2" x 7" air brakes  
8.25 x 22.5 10-hole disc wheel  
Automatic slack adjusters  
One-piece oil seals  
Red & white conspicuity markings  
Color: Trail 2-part polyurethane  
Blasted prior to paint King

**TK110HDG Advantage Plus Hydraulic Detachable**  
**13' 0" (16" KP setting W/110" swing) hydraulic detachable gooseneck**  
**2nd king pin setting (40" with 86" swing)**  
**PTO Hydraulics**  
**102" deck width**  
**Full-width deck**  
**20" loaded deck height w/6" ground clearance**  
**2 pr d-rings in knuckle trough and 2 pr d-rings in boom trough**  
**1 pr d-rings to be on flange of front slope of wheel area**  
**Bolster style wheel area**  
**Detachable wheel area with bolt-on front bolsters and horizontal pins**  
**No wheel covers**  
**Add upper brackets for hydraulic booster**  
**25,000-lb. (5/8" wall) axles**  
**60" axle spacing Air-ride susp. (adds to OAL}**  
**No ABS**  
**Duralite hub-piloted - Centrifuse drum (per complete axle)**  
**Steel wheels (per wheel)**  
**8.25 x 22.5 polished aluminum (per wheel)**  
**No spare wheel**  
**275/70R22.5 - 16 ply (per tire)**  
**No spare tire**  
**Wiring required for electric/hydraulic power unit on Hydraulic Booster**  
**One pair · 4" round amber strobes at rear ILO 3rd tail light w/switch**  
**4-pole socket at rear wired to clearance light**  
**Extra clearance light package cut into web O-X-O-X-O**  
**Remote flasher w/ battery back-up**  
**Stainless inserts around lights in tail channel**  
**Black S7203 with white decals (735-432-039)**  
**#60457. TK110HDG, 26 FT DECK ILO 25'-9**  
**Goes with TKFA1 D1426**

**DISCLAIMER**

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.