

HALE TRAILER BRAKE & WHEEL



A011374
VIN: 907601

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

Hydraulic tower: <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Powered with 13 HP Honda power pack <input checked="" type="checkbox"/> 12 inch lift	Dolly Overall length: 38ft 10 inches Width outside tire to tire : 120 inches Axles : <input type="checkbox"/> 3 <input type="checkbox"/> 1+2+2+1 <input type="checkbox"/> 3 + 2 <input checked="" type="checkbox"/> 3+ 3 Suspension : <input checked="" type="checkbox"/> Turner HT-250 <input checked="" type="checkbox"/> Scale-O-Matic <input checked="" type="checkbox"/> Dump valve front and rear group <input checked="" type="checkbox"/> Ball valve on air bag <input checked="" type="checkbox"/> Tire Max Pro inflation <input checked="" type="checkbox"/> Height override Valve <input checked="" type="checkbox"/> chain on front axles
Front tow bar: <input checked="" type="checkbox"/> Yes Frame : 100,000 PSI Steel X-Members: Fabricated Front fenders : <input checked="" type="checkbox"/> Yes Rear fenders: <input checked="" type="checkbox"/> Plastic	Axle location: Steering axles : <input checked="" type="checkbox"/> Yes, Qty: 3 Steering mecanism : <input checked="" type="checkbox"/> Front steer <input checked="" type="checkbox"/> Force steer with turn table <input checked="" type="checkbox"/> Suspension and axles with turn tables
D-Rings: <input checked="" type="checkbox"/> Yes Location: For lifting Bumper : <input checked="" type="checkbox"/> Long Mud flaps : <input checked="" type="checkbox"/> Témisko Location:	Steering control : <input checked="" type="checkbox"/> Automatic Axles : <input type="checkbox"/> D-22 <input type="checkbox"/> F-24 for 22.5 or 24.5 wheels <input type="checkbox"/> D-22 <input type="checkbox"/> F-24 for 19.5 wheels <input checked="" type="checkbox"/> D-22 <input type="checkbox"/> F-24 for 17.5 wheels
Lights : <input checked="" type="checkbox"/> Truck-lite round type (2/s) <input checked="" type="checkbox"/> 7 way plug <input checked="" type="checkbox"/> Strobe light in bumper <input checked="" type="checkbox"/> Beacon Light <input checked="" type="checkbox"/> Oversize load sign	Axle track : Brake type: <input checked="" type="checkbox"/> Drum brakes Seals : Stemco Guardian HP Bearings : Stemco Brake chambers: <input checked="" type="checkbox"/> TSE 30/30T Automatic slack adjusters: <input checked="" type="checkbox"/> Haldex Brake valve : Rockwell Wabco Brake lining : <input checked="" type="checkbox"/> CM20 Hubs : <input checked="" type="checkbox"/> 8 studs steel piloted hubs
Tool box : <input checked="" type="checkbox"/> Alum. Checkered plate Dimensions : Location : R/S and C/S Title holder : <input checked="" type="checkbox"/> Truck-lite Location : Paint : Color: black Color code: XXXXXXXXXX <input checked="" type="checkbox"/> Tape 100% Trim : Rim : <input checked="" type="checkbox"/> Natural	Drum : <input checked="" type="checkbox"/> Standard Rims : Qty : 24 <input checked="" type="checkbox"/> Aluminium machined finish <input checked="" type="checkbox"/> 17.5 x 6,75
Tires : Qty : 24 <input type="checkbox"/> 14 Ply <input type="checkbox"/> 16 Ply <input type="checkbox"/> S.B.C. Model : Michelin XTA2 ENERGY Size : 245/70R17.5 Hubodometer : <input checked="" type="checkbox"/> No Location :	
Special 200 ft of Electrical and rubber air line Flag holders in bumper Guillotine Type door on toolbox to fill power pack gas tank Wireless remote for steering with antena Wired remote for steering Tow bar at front with spring assist Loading bunk Power pack on R/S toolbox Spring to hold up tow bar Tow point at rear for pushbar Gladhands with shut off valve on dolly to be able to lock the air in	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.