

HALE

TRAILER

BRAKE & WHEEL

Hale Trailer Brake & Wheel

A011461

VIN: 021998

XL SPECIALIZED TRAILERS

XL 120 Step Deck Extendable

OVERALL LENGTH 53'
OVERALL WIDTH 102"
CAPACITY 120,000 LB DISTRIBUTED; 100,000 LB IN 10' CLOSED
WEIGHT +/- 3% 0,000 LB

GOOSENECK

LENGTH 11' 6" NARROW GOOSENECK
KINGPIN SETTING 16" REMOVABLE
SWING CLEARANCE 102"
5TH WHEEL HEIGHT 52"
DECKING NONE
STAKE POCKETS NONE
LANDING GEAR 2 SPEED W/ HANDLE ROAD SIDE
FLIP NECK FRAME REINFORCEMENT, AIR, BRACKETS, ELECTRICAL FOR 72" FLIP NECK
72" FLIP NECK

MAIN DECK

LENGTH 41' 6" EXTENDING TO 64' 4"
LOADED DECK HEIGHT 33" WITH OPEN WHEELS
DECKING 1 1/8" APITONG DECKING, FLUSH
CROSSMEMBER 4" JR. I-BEAM ON 12" CENTERS
SIDE BEAMS 6" MILLED SIDE RAILS
STAKE POCKETS 24" O/C WITH 5/16" X 2" RUB RAIL W/ SINGLE PIPE SPOOLS
D-RINGS (7) PAIR OF PAN STYLE D-RINGS ON MAIN DECK - EVENLY SPACED
(7) PAIR OF FLAT D-RINGS AT BOTTOM KNEE BRACES
AXLES (3) 25,000 NOMINAL, 77 1/2" TRACKING
SUSPENSION HENDRICKSON / 25,000 AIR
AXLE SPACING 60"
ABS NONE WITH SPRING BRAKES ON 1 AXLE
TIRES MICHELIN 245 / 70R / 17.5
WHEELS 6.75 X 17.5 STEEL INSIDE / ALUMINUM POLISHED OUTSIDE DISC WHEELS
BRAKES 12 1/4" X 7 1/2"
DRUMS HUB PILOT / OUTBOARD DRUMS
ELECTRICAL 12V SEALED GROTE SYSTEM WITH 3 TAIL LIGHT ALUMINUM PACKAGE
(1) PAIR OF BENT D-RINGS IN TAIL CHANNEL

PAINT

BLACK

ADDITIONAL

RAISE AND LOWER VALVE & LIQUID FILLED AIR GAUGE LOCATED IN REAR DRIVER SIDE BOLSTER
LED LIGHTING - STANDARD
(1) PAIR OF EXTRA CLEARANCE LIGHT AT START OF MAIN DECK
DUST SHIELDS
FRAME REINFORCEMENT, AIR, ELECTRIC, & BRKTS FOR 2 AXLE POWER BOOSTER
4" AMBER STROBE LIGHT TO BE USED AS 3RD STT
MANUAL RIDE HEIGHT CONTROL
(1) 4-WAY PLUG IN EACH CORNER OF MAIN DECK
(1) 4-WAY PLUG IN REAR BOLSTER - BOTH SIDES
LIMIT CHAINS ON ALL 3 AXLES
PSI TIRE INFLATION SYSTEM ON ALL 3 AXLES

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.