

HALE

TRAILER

BRAKE & WHEEL



Resale Inventory
A011888
VIN: 575821

SALES | RENTALS | PARTS | SERVICE

- | | |
|-------------------------------------|---------------------------------------|
| Allentown, PA: 800-383-8894 | Jacksonville, FL: 800-828-3055 |
| Baltimore, MD: 888-601-7500 | Little Rock, AR: 833-424-8944 |
| Boston, MA: 800-854-5310 | Portland, ME: 800-325-4253 |
| Concord, NC: 800-438-2250 | Richmond, VA: 866-839-3495 |
| Delmar, DE: 866-486-1400 | Scranton, PA: 800-569-1400 |
| Des Moines, IA: 888-673-5011 | Springfield, MA: 800-854-5306 |
| Elkton, MD: 800-544-7127 | Voorhees, NJ: 866-315-0235 |

HaleTrailer.com | @haletrailer
800-232-6535 *FINANCING AVAILABLE

Magnitude 55HFLD 26 60 Air Tridem (Flat Level Deck) (Model: MAGNITUDE55H)	
	Est. Wt.: 28,339# +/- 3%
Capacity: 55 tons in 12-foot length with 4 axle close coupled or single axle stinger - GAWR and tire ratings determine legal payloads	
Load Base: 12-foot rigid 2-point load centered in deck area	
Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs	
Compatibility: Designed to accept 55/60 rear axle, spreader and/or 23 inch flip box	
Gooseneck Design: Hydraulic removable non-ground bearing design	
Loaded Fifth Wheel Height: 50 inches nominal with 5 ride height positions	
Swing Radius: 102 inches (11 feet 11 inches overall gooseneck length) - NGB	
Alternate Kingpin: Removable kingpin at 102 inch radius	
Flip Box: 23 inch Flip Box Serial Number Z539-Z646	
Power Source: 13 HP (min.) Gasoline powered auxiliary power unit	
Electrical Receptacle: J560 7-pin connector	
Deck Width: 8 feet 6 inches overall (unless optional deck width is selected)	
Deck Length: 26 feet clear deck length	
Loaded Deck Height: 22 inches with 6 inches ground clearance	
Flooring: 2 inch nominal wood - side rails only	
Front Ramps: Manual front approach ramps with risers	
Front Bogie Ramp: Included	
Extension Brackets: 12 pair - 24 total removable swing type, 1 pair - 2 total heavy duty removable hook-on type (26 swing type, 1 hook-on type on 27 foot deck)	
Deck to Bogie Connection: Fixed	
Tool Box: 2 Fully covered trays in front of deck between mainbeams with lockable covers.	
Crossmembers: Recess last 3 crossmembers in deck	
Number of Axles: 3 axles	
Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
Axle Spread: 60 inches (between axles) **See Deck Length Notes	
Dust Shields: None	
Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
Suspension: Air ride	
First Axle Lift: None	
Third Axle Lift: Air lift	
Tires: 275/70R 22.5 OEM Standard	
Wheels: 8.25 x 22.5 steel disc - hub-piloted	
Bolsters: Recessed load bearing between all axles and rear of last axle	
Covered Rear Bogie: Weld-on load bearing wheel covers	
Bumper: Heavy duty V-style rear bumper	
Width: 8 feet 6 inches	
Spreader: None	
Flip Axle: 51/60 60 rear flip axle - steel disc wheels Serial Number 75519-75526	
Dust Shields on Flip Axle: None	
Electrical System: DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes	
Paint: Fontaine black polyurethane enamel	

Lash Rings: 14 pair - 28 total	
Rear Bogie Height: 40 7/8 inches to top flange - 36 5/8 inches to top of bolsters	
Boom Trough: V-style boom trough with bolt-in V pan	
Mechanical Ride Height Control: Mechanical ride height control valve (Whittle Style)	
Manual Dump Valve: Manual Dump Valve (Push Pull)	
Flag Holders: Flag holders - 1 pair located at front of deck and on rear bumper	
Accent Package: None	
Liquid Filled Gauge: Liquid filled air gauge installed	
VIN Plate: Bilingual VIN plate	
Registration/Document Holder: Install registration/document holder	

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.