



Hale Trailer Brake & Wheel

A011898

VIN: 001826



20ANR

20 Ton Tandem Air Tilt/No Ramp

Tags

Base Weight: 9,820

TRAILER

Overall Length 34 ft. 7 in.
 Overall Width 102 in.
 Weight lbs +/- 2% 10366, including options
 A-Frame 6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam
 Hitch 3 in. pintle eye, adjustable 5 position 17 in. to 28 in.

DECK

Deck Length 21 ft.
 Loaded Deck Height 34 in.
 Main Frame Hi-Tensile Wide Flange 14 in. @ 22
 Cross Members Hi-Tensile 6 in. Channel @ 8.2
 Side Rail Hi-Tensile 8 in. Channel @ 11.5 open on inside
 Air Tilt Deck 2 Air Bags
 Floor 1 3/8 in. x 7 in. Keruing Shiplapped
 Landing Gear Dual Holland Mark V 2 Speed
 Rear Wedge Style bumper with air assisted tilt deck for ground loading

SUSPENSION/AXLES

Axles 25,000 lbs Capacity 77.5 in. Track
 Spread 49 in.
 Suspension Ridewell RAR 260 Underslung Air ride 25,000lbs. (includes air gauge and dump valve)
 Alum Air Tank *NPO*: c/w drain plug and cable
 Brakes Quick Change 12 1/4 in. x 7 in.
 Brake Chamber #3030, All Axles
 Air Brake System 2S/1M
 Bearings Oil Bath
 Slack Adjusters Automatic
 Hubs & Drums 8 Stud Unimount C / W Cast Drums
 Tires 235/75R17.5 16 ply
 Wheels Alum. Wheel Pkg. 17.5 (4 steel, 4 polished)

BEAVERTAIL

Length 6 ft. @ 8 degree slope, Self Cleaning Outside , Planked in inside

GENERAL SPECIFICATIONS

Electrical System Modular, Vapor Proof GROTE Ultra Blue
 Lights LED CMVSS 108 / FMVSS 108
 Front Connector SAE J560 7 Pin
 Finishing Preparation by Steel Shot Blast, Commercial / Industrial Topcoat, Oven Baked
 Color Black
 Mudflaps 1 set of BWS at rear
 Toolbox Full A Frame mounted with solid bottom and cover
 Load Securement 7 pair of D-rings: 6pr on main deck, evenly spaced; 1 pr on main beam on headboard
 Fenders 3/16 in. deck plate
 Ladder *NPO*: Ladders; 1 step at front on driver's side
 GVWR Rating is based on standard configuration and a 15% Tongue weight distribution

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
 Equipment availability, prices and specifications are subject to change without notice.