

TKMB2 Mechanical booster; axle, 9 & 10 axle configuration, 50,000lb cap

STANDARD EQUIPMENT 27, 000 lb. axles (3/4 wall) 16 1/2" x 7" air Brakes

Oil seals

Air ride suspension

Electrical

Lights

Misc.

Paint

Custom Options

MF-80 or T-1 equivalent steel construction 14' 1" axle spacing from center of the last axle on the trailer to the first axle on the booster

Drop-leg jack

102" overall deck width

Rubber mounted sealed LED lights and sealed

harness system

Electrical system per DOT regulations

Mud flaps

Red & white conspicuity markings

Liquid-filled air gauge

Manual raise and lower valve (not standard on TKAB)

Color: Trail King 2-part polyurethane

TKMB2 Mechanical booster; 2 axle, 9 & 10 axle configuration 50,000 lb cap **Open Deck Axles** T.P. axles (same inner & outer bearings)(avail. for 161/2" x 7" brakes only) (per

complete axle)

Hub/Drum Duralite hub-piloted - Centrifuse drum ILO Std (per complete axle)

Wheel Size 8.25 x 22.5 10 -hole disc wheel

Wheel Finish (inside) 8,25 X22.5 machined aluminum ILO Std steel wheels Wheel Finish (outside) 8.25 x 22.5 polished aluminum ILO Std steel wheels

4-pole female electrical socket wired to clearance light in light channel

One pair of 4" round amber strobes at rear w/ on/ off switch wired to blue wire

Flag holders (per pr.)

Brackets only for Removable oversized load sign

Flag holders (per pr.) In tail channel

Brackets only for Removable oversized load sign

Bright White with black decals (735-481-053)

Goes with TK80J C5972 & TK120HDG C5973

Timken bearings, per complete axle