

HALE TRAILER BRAKE & WHEEL



Resale Inventory
A012052
VIN: 049706

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

TK120LPSD-HS

STANDARD EQUIPMENT TK-120LPSD-HS Gen 3 steering dolly

Capacity: 120,000 lbs.

Width: 10' 0"

Suspension: Air ride with raising and lowering

Tire Size: 235/75R x 17.5 radials

Wheels: 6.75 x 17.5 machine finished aluminum disc 60" axle spacing, 14' 1" group spacing

Front steer design

Hydraulic steering

Auto steer or manual steer

34° 1st axle in auto, 39.5° 1st axle in manual

Adjustable steering ratio

Manual steer by wireless or wire-type remote

Auto-alignment after manual steer

12.25 x 7.5 brakes (20,000 GAWR)

Individual Poly fenders on all axles

13 H.P. Honda self-contained unit

Auxiliary air outlet for power tools

Power beyond for hydraulics

Wide load sign brackets at rear

Support plate for gooseneck support arm

Grote sealed wiring harness

Provisions at rear for connecting to front schnable

Lightweight push bar and brackets for positioning on site

Spring Brakes on 3 axles

Blasted prior to paint

Paint: Trail King 2-part polyurethane

Estimated Weight: 22,430 lbs

62506 TK120LPSD-HS, Standard specs per 62506 specification sheet

62506 TK120LPSD, "P" type spindle, Synthetic Grease, Timkin Bearing ILO std, 6 axles

61721, General, Betts PS-1 registration holder ILO std

62835, TK120LPSD-HS, Delete Hat box, Frame to be "straight", no double drop

62836, TK120LPSD-HS, Add provisions at rear for connecting to Front Schnable neck for return

61724, General, Install (2) two pin pigtailed out of rear channel

63404, General, Lighted removable oversize load sign

63664, TK120LPSD-HS, Light weight push bar and brackets for positioning the dolly on site

64803, General, Electrical socket for use with option 63404, lighted oversize load sign

Black 57203 with white decals (735-432-039)

Goes with TK100JLW K9705, TKFront Schn Gn K9706A and TKRear Schn Gn K9706B

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.