

HALE TRAILER BRAKE & WHEEL



Resale Inventory
A012260
VIN: 42775

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Infinity SX Flatbed (Pkg. Trl.)

A. DESIGN INFORMATION

Overall length	48 ft.
Frame Rating	80,000# Distributed Frame Capacity- 55,000# Concentrated in 5 ft.- GAWR and Tire Ratings Determine Legal Payloads
Framework	Min. 130 flanges and Hi-Tensile webs W/Aluminum Extrusion Siderails, Aluminum Front Skirt and Rear Skirt
Width	102 in.

B. PLATFORM

Flooring	1-1/8 in. Aluminum w/4 Apitong nail strips
Crossmembers	4 in. @ 3.19#/Ft. Steel on 12 in. Centers
Coil Package	2 Stub and 2 Full Depth Steel Crossmembers to Reinforce Floor and Frame when Hauling Single Coil- Coil Location Decal at Single Coil Position on Both Sides of Main Beam Web
Side Rails	Aluminum Extrusion
Stake Pockets	Aluminum located on 24 in. centers on sides, 3 recessed aluminum in rear, None on Front; Double pipe spools located between stake pockets on sides
Rubrail	3/8 in. x 3 in. Aluminum on sides, None on rear
Main Beams	Fabricated Steel I-beams; 3/8 in. x 5 in. (min. 130) Top & Bottom flanges with continuous welds on both sides; 25 in. deep one piece web
Kingpin	Double Spool type set 30 in. from front with sloped upper coupler plate
Loaded fifth wheel height	49 in
Landing gear	Fontaine 2 speed, square leg with 10 in square cushion foot- Steel Diagonal, Cross & Rear Bracing
Knee Braces	Formed Steel Wing Type with Triangular Cut-outs

C. UNDERCARRIAGE

Number of axles	(2) Intraax
Axle Spindle	Tapered
Brakes	16 1/2 in. x 7 in. Air with Quick change feature; Spring parking brakes with Automatic slack adjusters

ABS	Meritor 4S/2M (no tool or cable) wired to center pin of Std. 7-way socket
Axle spread	122 in. Spread- Set at Rear
Hub and Drums	10 Hole Hub Piloted - Outboard Cast Drums
Wheel Ends	Grease in hubs- *5 Year Wheel End Warranty
Wheels	24.5 x 8.25 Steel Disc
Tires	11R 24.5 14 Ply
Tire brand	O.E.M. Std.
D. SUSPENSION	
Suspension	Intraax AA230 Air Ride Buttoned up With 5 Year Warranty*
Dump Valve	Electric Dump Valve (Rear Axle, wired to Aux 7-way socket)
E. GENERAL	
Front Corners	Diagonal Deck Corners with Light Mountings
Electrical System	Sealed Harness & LED Lights: 5 marker lights per side including mid-turn; 3 marker lights on rear, 3 stop, tail, turn per side on rear
Paint	All Steel Primed and Painted Black Plural Component Urethane
Conspicuity Tape	Per NHTSA Specs Installed on Rubrail on Sides
Bumper	Bolt-on Type Steel Which Meets Underride Requirements; Steel Corners
Mudflaps	Two Sets with Fontaine Logo
Dock Bumpers	One Pair Vertically Mounted on Rear Corners
Spare tire carrier	Not Included- Holes in Frame on Both Sides to Allow Future Bolt-on Installation
Winch Track	Full length Integrated Aluminum Winch Track on Road Side
Sliding Winches	(12) Sliding Winches for Integrated Aluminum Winch Track on Road Side (Straps Sold Separately)
Chain tie downs	15 Pair Recessed in Siderails
Tarp Boxes	Not Included- Holes in Frame on Both Sides Between Axles to Allow Future Bolt-on Installation
Estimated empty weight	10738 lbs. +/- 3%

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.