



Resale Inventory

A012263

VIN: 32569

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Talbert Manufacturing, Inc.

Model: T(3)-40-SRG-T1

Capacity in tons: 40



1. GOOSENECK

Gooseneck design	Mechanical removable
Loaded 5th wheel height	49"
Swing radius	80"
Electrical receptacle	Seven pin connector
Gooseneck platform	Full width (8'-6" 0/0) covered with 1-1/8" shiplap apitong with three (3) lashing slots each side
Rollers	At front -38-1/2" I/I of flanges
Additional gooseneck specifications	Aluminum rock guard ILO mud flaps

2. DECK

Deck section design	Four beam
Deck section length	30'-0" (29'-6" clear)
Deck section width	8'-6"
Mainbeams	12" T-1A
Loaded road clearance	8"
Loaded deck height	20"
Flooring	1-1/2" apitong, full width, secured with floor screws
Gooseneck/deck connection	Horizontal sliding pin and fixed teardrop with remote lock
Deck/rear bridge connection	Fixed/welded
Outriggers	12" swinging and removable with double hook-on at front of deck
Reinforced top flange of sidemember	None
Slope front of deck top down	With smoothplate & traction bars
Auxiliary load securement	None
Additional deck specifications	Auxiliary crossmembers
Heavy duty front folding ramps	None
Expanded metal	None

3. REAR BRIDGE

Rear bridge section width	8'-6"
Loaded rear bridge height	43"
Number of axles	2
Axle capacity	25,000#
Axle spacing	50"
Brakes	16-1/2" X 7" air actuated with spring brakes on one axle
Anti-lock brake system	Two (2) sensor, one (1) modulator system
Wheels	Ten (10) stud; 285.75mm BC steel disc hub piloted system with oil seals
Tires	Eight (8) 255/70R22.5 (H) 16PR radials
Suspension	Ridewell air
Air Lift	None
Exhaust Valve	None
Manual raising & lowering	Hand valve type located in rear light panel

Scale-O-Matic	None
Hubodometer	None
Suspension options	None
Wide center bolster	None
Rear half bolster	None
Front bridge ramp	Sloped with plate and traction bars
Rear bridge platform	Full width (8'-6" 0/0) covered with 1-1/8" shiplap apitong
Additional rear bridge specifications	Four (4) lashing slots each side Flush connections for future 3rd axle

4. GENERAL

Lights and wiring	12 volt LED system including mid-turn lights, license plate light regular
Paint	Standard Talbert black
Lash rings	10 - 5 each side of deck
Capacity rating	80,000# evenly distributed; 70,000# in 10'-0" when used with future 3rd axle
Additional general specifications	None

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.