



FRAMELESS DUMP

Hale Trailer Brake & Wheel

A012327

VIN: 80975



Length	39' (1) (6)	BODY SPECIFICATIONS		Body	
Width	102"	Tarp	NONE	Accessories	BLACK TAPE IN TOP AND BOTTOM RAILS (5)
Side Height	56" SOLID (2)	Bow Holders	NONE		
Top Rail	8"	Tarp Bows	NONE		
Side Mat'l	.230"	Tarp Basket	NONE		
		Tarp Hooks	NONE	TAILGATE	
		Bulkhead Mat'l	.250"	Height	FULL - HORIZON SHAPE
Side Options	NONE	Bulkhead	SLOPE NOSE	Mat'l Thkness	3/16" SHEET/POST DESIGN
Floor Mat'l	1/4" NOMINAL + LINER (3)	Options	NONE	Slope	NONE
Crsmbr Spacing	NONE	Body Fenders	NONE	Hinges	OVERSLUNG
		Ladders (Out)	REAR DRIVER SIDE	Side Swing	NONE
			RUNG STYLE LADDER	Gateseal	RUBBER
Floor Options	NEW STYLE BOTTOM RAILS WITH INTERNAL BRACE	Inside	NONE	Safety Latch	ONE 45 DEGREE EACH SIDE
Tailgate Control	AIR / FRAME + ELEC CC (4)	Shovel Hgr	NONE	Coal/Grain Door	20" WIDE
Body Pkg Options	NONE	Light Panel	FULL - LED	Coal Chute	NONE
Vibrator	NONE	Marker Lights	LED - 3 PAIR	Gate Options	NONE
Mudflaps	STD + ACROSS REAR CHASSIS	MMTS	PIVOT BRACKET		
		Apron	NONE		

CHASSIS SPECIFICATIONS

Model	TANDEM	ABS	4S / 2M	Tire Carrier	NONE
Length	130 3/4"			Landing Gear	2 SPEED JOST ALUMILITE X D/S CRANK
Width	102"				
Draft Arms	226" ALUMINUM	Independ. Susp(s)	NONE		
Hoist	85-265 + REMOTE GREASE ZERK TO TOP PIN D/S			Elec Coupler	7 WAY + 7 WAY ISO
King Pin Setting	16"	Distance:			
		From:		Hyd Hose Fitting	WINGNUT
5th Whl Ht	49"			Hyd Hose Length	108"
		Controls		Tow Hooks	NONE
Rear Axle Setting	25-3/4"			Paint	BLACK NOTE (5) GALVANIZED HANGERS
K/P To Rear Axle	427"	Location			
Suspension	AAT30K / E2-1	Axle(s)			
Susp Control	FRAME SWITCH + ELEC CC			Chassis Options:	
Susp Spacing	52"	Accessories			MUDFLAP ON REAR
Susp Options	GALVANIZED HANGERS				
Springs	AIR	Brakes			
Axles	TP SPINDLES	Drums			
Accessories	TIREMAAX PRO "LB"	Hubs			
Brakes	16-1/2" x 7"				
Drums	LIGHT WEIGHT	Wheels			
Hubs	10 S LWSTEEL - PILOT				
		Tires			
Wheels	8.25 x 22.5" ALUM HP				
Tires	11R 22.5" BS R196				

REMARKS: PRICING SUBJECT TO CHANGE 12 WEEKS PRIOR TO ESTIMATED BUILD TIME.

(1) 39'-1" (MEASURED FROM FRONT OF COUPLER PLATE TO BACK OF REAR POCKET)

(2) 56" SOLID (MEASURED FROM HORIZONTAL PLANE FROM TOP RAILS TO CENTER OF FLOOR - LOWEST POINT)

(3) STD 1/4" ALUMINUM FLOOR + 1/4" x 101" WIDE UHMW (DURAPRO) LINER w/ 3/8" LAST 4'

(4) GATE LATCH BAR REMOTE GREASE ZERK FITTINGS TO REAR D/S.

WEIGHT: 10,420

(5) INSTALL BLACK TAPE IN TOP AND BOTTOM RAIL BOTH TAPE GROOVES EACH RAIL.

CHANGE 1

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.