

HALE TRAILER BRAKE & WHEEL

Hale Trailer Brake & Wheel

A012331

VIN: 235811JDM



OVL Length: 26
Appx Wgt +/-:
5,700 lbs

FT-16 IT-I Drop

Item Type	Options	Description	Add Qty	Unit	Total Qty
Base Trailer		FT-16 IT-I		Each	0
Stationary Deck	✓	Stationary Deck	1	Feet	5
Deck Length		Add Tilt Deck Length (Includes 2' Steel Punch Plate Approach)		Feet	16
Stationary Deck Type		White Oak 2" Nom		Std	1
Deck Type		White Oak 2" Nom		Std	1
Appx Deck Height		22.5" Loaded, 24.5" Unloaded		Inches	1
Width		102" OD, 81" ID		Std	1
Tie Downs		D-Rings, 5/8" Straight		Std	10
Tie Downs	✓	Rub Rail & Stake Pockets (along stationary deck Only*)		Feet	5
Brakes		Electric, FSA (Fwd Self Adj) On All Axles		Std	1
Axles		8K Oil Bath Drop		Std	2
Suspension		Spring, 36" Spread		Std	1
Tires & Wheels		215/75R 17.5 H, 8 Bolt [17.5 x 6.75] Plate Wheel		Each	4
Hitch Length		Center of Coupler to Headboard, Appx		Feet	5
Hitch Type		2.5" Adjustable Lunette Eye/Pintle, [C] 42,000 lb Plate Mount (5/8" Bolt)		Std	1
Hitch Height		Approximate Adjustment Hitch Range 14.5" to 23.5" (21.5" to 26" if Hyd)		Std	1
Jack	✓	Dual 12K w/ Spring Loaded Drop Leg		Pair	1
Plug		7 Pole RV		Std	1
Lights		LED,4 tail light system, Sealed Wiring Harness (Tail lights located on rear of fenders)		Std	1
Trailer Color	✓	Viper Red # CCA945383 (White Felling Decal)		Opt	1
Standard		3/8" Safety Chains, Grade 70		Std	1
Standard		Document Holder		Std	1
Standard		Dual cushion cylinders		Std	2
Attachment Rack	✓	Attachment Rack (Removable)-54" Deck height, full width of deck (ID of uprights is OD of stationary), angle lip up w/rub & stake front and sides (Black w/std decking unless otherwise optioned) **2,500 lb Max Capacity**	1	Feet	5

Item Type	Options	Description	Add Qty	Unit	Total Qty
Attachment Rack	✓	Attachment Rack Bolt-On Shovel / Broom Holder (3 Tubes) (curb side)		Each	1
Option	✓	Toolbox, Medium 57" x 16" x 11", Bolt on with Lockable Cover, 4.9 Cu Ft		Each	1
Option	✓	Pallet Fork Holders Mounted 36" O.D. of tubes with Fork Securement Chains		Pair	1
GVWR		18,400 lbs		Std	1

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.