

TK80J Jeep; No ABS, 80,000lb cap (2 axles)

STANDARD EQUIPMENT	Electrical system per ICC/DOT regulations
Outboard 10-hole pilot mount	Rubber mounted sealed LED lights and sealed harness
2-27,000 lb. axles (3/4" wall)	system
16 1/2" x 7" air Brakes	48" sliding 5th wheel
Oil seal hubs	Red & white conspicuity markings
Air Ride Suspension	Color: Trail King 2-part polyurethane
Automatic slack adjusters	Liquid-filled air gauge
	Air ride raise and lower kit -

<u>Quantity</u>

<u>Category</u>

Description

Base Trailer

1	Open Deck	TKSOJ Jeep; No ABS, 80,0001b cap (2 axles)
1	5th Wheel Height	50" 5th-wheel height
1	King Pin	16" kingpin setting w/84" swing clearance
1	Landing Gear	2-speed park stands ILO std (crank curb side)(Sth wheel)
1	Deck Width	96" deck width
2	Axles	T.P. axles (same inner & outer bearings)(avail. for 16 1/2" x 7" brakes only) (per complete axle)
1	Axle Spacing	54" axle spacing

i:

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.