

HALE

TRAILER

BRAKE & WHEEL



Resale Inventory
A012557
VIN: 28932

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

Velocity TX Drop Deck 48' Wide Spread Air (Model: HCVTX12WSA)	
	Est. Wt.: 11221#
Overall Length: 48 feet x 102 inches	
Suspension Type: Wide spread air	
Deck Lengths: 10 feet front and 38 feet rear	
Frame Rating: 80,000 lbs distributed - GAWR and tire ratings determine legal payloads	
Rear Deck Height: 40 inches - loaded	
Flooring: 1 1/8 inch aluminum with wood nailer strips	
Crossmembers: 18 inch centers front deck / 16 inch centers rear deck - 4 inch jr. I-steel	
Side Rails: 6 inch structural channel @ 6.5 lbs/ft	
Stake Pockets: 3/16 inch steel on 24 inch centers	
Pipe Spools: Double between stake pockets	
Rubrail: 3/8 inch x 2 1/2 inch steel	
Main Beams: 130K load bearing flanges	
Kingpin: 18 inches	
Loaded Fifth Wheel Height: 49 inches	
Landing Gear: OEM standard	
Knee Braces: Fabricated on approx. 60 inch C/C	
Bulkheads: None standard	
Bulkhead Pockets: 4 - F-5 DOT-type steel	
Number of Axles: 2	
Axle Spindle: Tapered	
Brakes: Spring brakes, auto slacks	
Air Line Filters: (2) Meritor In-line type installed	
ABS: 4S/2M - no cable or tool	
Axle Spread: 122 inches - set at rear	
Hub and Drums: 10-hole hub-piloted with outboard cast drums	
Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***	
Wheels: 22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD	
Tires: 255/70R 22.5 16PR OEM standard	
Tire Inflation System: None standard	
Suspension Detail: AANL23K Intraax air ride	
Auto Glad Hand Dump: Installed	
Electric Dump Valve: Wired to 7-way auxiliary socket to dump rear axle	
Front Corners: Tapered	
Electrical System: LED: 3 lights/side, 2 lights/side on rear- STANDARD	
Paint: Black urethane with Velocity decals - STANDARD	
Conspicuity Tape: Per NHTSA specs - installed on rubrails	
Bumper: Weld-on type - meets override requirements	
Mudflaps: 2 sets OEM standard; Spring loaded brackets behind front axle	
Winch Track: Steel on road side: 8-foot front deck and full length on rear deck where possible	
Sliding Winches: 12 standard - without straps: 2 front deck and 10 rear deck	
Winch Straps: None standard	
Container Locks: (4) Retractable to accept (1) 10' Container	
Dock Bumpers: 1 pair rubber on rear	
Spare Tire Carrier: 1 standard - mounted between lower gooseneck beams	
Hubodometer: None standard	
Registration Holder: None standard	
Tool Box: None standard	
VIN Plate: Bilingual US/Canadian VIN plate	

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.