Base Model #: CW48
components description
CAPACITY 48FT 2Axle GVWR 67,470LBS
OVERALL LENGTH 48'
OVERALL WIDTH 8' 6" - 48ft
OVERALL HEIGHT FRONT 13'-6"= Flat Top tarp system included in height UPPER
COUPLER HEIGHT 48"
UPPER COUPLER PLATE 5/16" Plate
KING PIN SETTING 36"
SWING CLEARENCE 90"= 36KP
LANDING GEAR Two Speed
SUSPENSIONS Air Ride-Hendrickson Intraax 46K - 2 Axle Slider (Manual Dump)
SUSPENSION LOCATION Slider/Variable
AXLES (2) 22,500K Capacity - Type 30 Chambers - Auto Slacks - ABS(Disc Axles)
Disc Axles.
AXLE SPACING 49"
LIFT AXLE Air Lift Front Axle - Air Ride
Operate Lift Through Cab and Manually.
WHEELS Disc - Hub Piloted- 22.5- (Steel)
TIRES 11R22.5 - Firestone FT455
FRONT TYPE 10" Diagonal
FRONT MATERIAL Stainless Steel - Front and Corners - Mirror Finish LADDERS
Aluminum Nose Only
REAR DOOR TYPE Heavy Duty Dry Van Style Door
Quad Door Locks.
REAR DOOR MATERIAL Galv./Quilted Stainless Steel Plywood
SIDE SHEET MATERIAL .063 Aluminum - Smooth
INTERIOR LINING None
SIDE SHEET COLOR Black - Pre-Painted
SIDE POST Extruded Aluminum 16" Centers - "Round" Post Design
LOWER RAIL Heavy Duty Aluminum Lower Rail
FLOOR Keith Walk Floor Sys - 3/16"(2188)- STD Deck - Alum. Sub-48' + 3,446#

Parker 6100-16 Wing Type Series Fittings.
Male On Pressure Side and Female on Return Side.
FLOOR SILLS 4" Steel - Wax-Dipped I-Beam w/ Undercoating
SILL SPACING 12"/12"/12" Heavy Duty / Live Floor
DUST SHEILDS None
ANTI-SAIL MUD FLAPS Behind Rear Axle
BUMPER H. D. 3" x 4" Non-Push Bumper(Flush Rear Frame)
Stainless Steel Flush Rear Frame.
Flange Mount Anti-Theft S/T/T.
TARP SYSTEM Shur-Co Flat Top Solid Shur-Lok -Frt&RrCap-0Bows-22oz-2RidgeStraps-48'-102WD
ADDITIONAL TARP BOWS None
TARP COLOR BLACK
LIGHTS Sealed Wiring Harness W/ LED PKG
(5) Marker Lights Per Side Along Lower Rail.
(5) Marker Lights Per Side Along Upper Rail Below Tarp.
PAINT Black - Fifth Wheel and Catwalk
Custom (3) Straight Sidewall Stiffeners
Reference Serial # 32379