



## Hale Trailer Brake & Wheel

A012771

VIN: 021995

### XL SPECIALIZED TRAILERS

#### XL 120 Step Deck Extendable

OVERALL LENGTH 53'  
OVERALL WIDTH 102"  
CAPACITY 120,000 LB DISTRIBUTED; 100,000 LB IN 10' CLOSED  
WEIGHT +/- 3% 0,000 LB

#### GOOSENECK

LENGTH 11' 6" NARROW GOOSENECK  
KINGPIN SETTING 16" REMOVABLE  
SWING CLEARANCE 102"  
5TH WHEEL HEIGHT 52"  
DECKING NONE  
STAKE POCKETS NONE  
LANDING GEAR 2 SPEED W/ HANDLE ROAD SIDE  
FLIP NECK FRAME REINFORCEMENT, AIR, BRACKETS, ELECTRICAL FOR 72" FLIP NECK  
72" FLIP NECK

#### MAIN DECK

LENGTH 41' 6" EXTENDING TO 64' 4"  
LOADED DECK HEIGHT 33" WITH OPEN WHEELS  
DECKING 1 1/8" APITONG DECKING, FLUSH  
CROSSMEMBER 4" JR. I-BEAM ON 12" CENTERS  
SIDE BEAMS 6" MILLED SIDE RAILS  
STAKE POCKETS 24" O/C WITH 5/16" X 2" RUB RAIL W/ SINGLE PIPE SPOOLS  
D-RINGS (7) PAIR OF PAN STYLE D-RINGS ON MAIN DECK - EVENLY SPACED  
(7) PAIR OF FLAT D-RINGS AT BOTTOM KNEE BRACES  
AXLES (3) 25,000 NOMINAL, 77 1/2" TRACKING  
SUSPENSION HENDRICKSON / 25,000 AIR  
AXLE SPACING 60"  
ABS NONE WITH SPRING BRAKES ON 1 AXLE  
TIRES MICHELIN 245 / 70R / 17.5  
WHEELS 6.75 X 17.5 STEEL INSIDE / ALUMINUM POLISHED OUTSIDE DISC WHEELS  
BRAKES 12 1/4" X 7 1/2"  
DRUMS HUB PILOT / OUTBOARD DRUMS  
ELECTRICAL 12V SEALED GROTE SYSTEM WITH 3 TAIL LIGHT ALUMINUM PACKAGE  
(1) PAIR OF BENT D-RINGS IN TAIL CHANNEL

#### PAINT

BLACK

#### ADDITIONAL

RAISE AND LOWER VALVE & LIQUID FILLED AIR GAUGE LOCATED IN REAR DRIVER SIDE BOLSTER  
LED LIGHTING - STANDARD  
(1) PAIR OF EXTRA CLEARANCE LIGHT AT START OF MAIN DECK  
DUST SHIELDS  
FRAME REINFORCEMENT, AIR, ELECTRIC, & BRKTS FOR 2 AXLE POWER BOOSTER  
4" AMBER STROBE LIGHT TO BE USED AS 3RD STT  
MANUAL RIDE HEIGHT CONTROL  
(1) 4-WAY PLUG IN EACH CORNER OF MAIN DECK  
(1) 4-WAY PLUG IN REAR BOLSTER - BOTH SIDES  
LIMIT CHAINS ON ALL 3 AXLES  
PSI TIRE INFLATION SYSTEM ON ALL 3 AXLES

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.