

# HALE

## TRAILER

### BRAKE & WHEEL

## Hale Trailer Brake & Wheel

A012831

VIN: 941002



Quantity	Description
	Reference: ART-60-40
	<p>Line: 001            Part: ART-60-40            ACE ROLL OFF TRAILER            NEW ACE ROLL OFF TRAILER - ART-60-40            Overall Length: 40' 11"            Container Frame Length: 40'            Kingpin to Last Axle: 34'            Rated 60,000 lbs. Lift Capacity            Container Size Range- 10'-40' Outside Rail Containers</p> <p><b>MAIN FRAME:</b>            12"X 4"X 1/4" Rectangular Tubing            12"X 4" Cross Members for Main Frame            Top Wrap: 1/2" X 4" Flat Bar Wear Pad            Bottom Wrap: 3/4" x 4" Flat Bar            1/4" Hollow Truss Mounted Below Main Frame with 1/2" X4" Bottom Wrap            (2) 1 1/4" Fixed Stops at Front of Trailer            (14) 3 1/2" Rollers Welded to Outside Frame            3/4" King Pin Plate with 3/4" Plate Supports &amp; 2" Round Bar Stiffener</p> <p><b>STABILIZER FRAME:</b>            4"X4"X 1/4" Tube with 4"x4"x3/8" Angle Wrap            Hinges: 2" Round Bar            28"x16"x5/8" Draft Arm Support Plates</p> <p><b>HYDRAULICS:</b>            (2) 8.5"- 4 Stage Telescopic Main Lift Cylinder 133,000 lbs. @ 2,400 PSI            (2) Ace Independent Reeves: 3 1/2" Rod 7" Bore Reeving Cylinder 88,000 lbs. ea.            Directional Valve with Pressure Gauges and Adjustable PSI – Set to 2,450 PSI            Hoses: 3/4" 3000 PSI Hoses with Nylon Covering            Hydraulic Pipes: 3/4" Steel Pipe</p>



Quantity	Description
	<p>Standard JIC Fitting on All Hydraulics NO HYDRAULICS IN REAR OF TRAILER</p> <p>CABLE AND AFFILIATED COMPONENTS: Cable-7/8" IWRC Cable, (4) Cable Clamps, Cable Button with Cast Ring Pulleys: 10" Sheave with 2.5" Pin (Qty 3) Pulley Block - Independent (2) Independent Pulley Track</p> <p>RUNNING GEAR: H900 50,000 lbs. Spring Single Point Suspension (Tandem) Suspension Hanger: 21" Fabricated I-Beam (2) 25,000 lbs. 5" Round Axles Brake Control: Spring Loaded 16" x7.5" ABS: 2S1M 10 Hole Uni-Mount Hubs &amp; Drums 10 Hole Uni-Mount Rims w/11R22.5 Tires Fenders- Rubber 2-Ply Ace Logo Rubber Mud Flap with Hook 2-Speed Landing Gear 120K lbs.</p> <p>LIGHTING &amp; SAFETY All L.E.D Lights All Lights Meet DOT #108 Lights &amp; Harness- Truck Lite Body Hoist Up Alarm- LED Strobe ICC REGULATED BUMPER- AIR ACTUATED Meets FMCSA 49 CFR § 393.86 (4) Nylon Tie Down Strap – More can be added*</p> <p>PAINT Cleaned, Primed, Painted Industrial Epoxy (Black) WARRANTY- In Years (5) On Main Frame – Excluded Rollers and Greaseable Items (1) All Hydraulic Components (1) on All Items Manufactured by Ace</p>



Quantity	Description
1	ea Axles & Suspension are subject to manufacturer discretion
1	ea Line: 002 Part: 654-3001-40 RR Roll-Off Complete 40' Hyd Roll Rite Tarping System (Hydraulic) - Hydraulic Ace Tower
1	ea Line: 003 Part: 221-1007 Automatic Tire Inflation Kit
1	ea Line: 004 Part: 115-1003-I Front Work Lights - Installed

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.  
Equipment availability, prices and specifications are subject to change without notice.