

# HALE

## TRAILER

### BRAKE & WHEEL

## Hale Trailer Brake & Wheel

A012832

VIN: 941003



| Quantity | Description  |
|----------|--|
| 1<br>/ea | <p>Ace ART-60-32 Roll Off Trailer<br/> <b>NEW ACE ROLL OFF TRAILER - ART-60-32</b><br/>           Overall Length: 33' 6"<br/>           Container Frame Length: 32'<br/>           Kingpin to Last Axle: 26' 7"<br/>           Rated 60,000 lbs. Lift Capacity<br/>           Container Size Range- 10'-32' Outside Rail Containers</p> <p><b>MAIN FRAME:</b><br/>           12"X 4"X 1/4" Rectangular Tubing<br/>           12"X 4" Cross Members for Main Frame<br/>           Top Wrap: 1/2" X 4" Flat Bar Wear Pad<br/>           Bottom Wrap: 3/4" x 4" Flat Bar<br/>           1/4" Hollow Truss Mounted Below Main Frame with 1/2" X4" Bottom Wrap<br/>           (2) 1 1/4" Fixed Stops at Front of Trailer<br/>           (12) 3 1/2" Rollers Welded to Outside Frame<br/>           3/4" King Pin Plate with 3/4" Plate Supports &amp; 2" Round Bar Stiffener</p> <p><b>STABILIZER FRAME:</b><br/>           4"X4"X 1/4" Tube with 4"x4"x3/8" Angle Wrap<br/>           Hinges: 2" Round Bar<br/>           28"x16"x5/8" Draft Arm Support Plates</p> <p><b>HYDRAULICS:</b><br/>           (2) 8.5"- 4 Stage Telescopic Main Lift Cylinder 133,000 lbs. @ 2,400 PSI<br/>           (2) Ace Independent Reeves: 3 1/2" Rod 7" Bore Reeving Cylinder 88,000 lbs. ea.<br/>           Directional Valve with Pressure Gauges and Adjustable PSI – Set to 2,450 PSI<br/>           Hoses: 3/4" 3000 PSI Hoses with Nylon Covering<br/>           Hydraulic Pipes: 3/4" Steel Pipe<br/>           Standard JIC Fitting on All Hydraulics<br/> <b>NO HYDRAULICS IN REAR OF TRAILER</b></p> <p><b>CABLE AND AFFILIATED COMPONENTS:</b></p> |



| Quantity | Description  |
|----------|--|
|          | <p>Cable-7/8" IWRC Cable, (4) Cable Clamps, Cable Button with Cast Ring<br/>           Pulleys: 10" Sheave with 2.5" Pin (Qty 3)<br/>           Pulley Block - Independent (2)<br/>           Independent Pulley Track</p> <p>RUNNING GEAR:<br/>           H900 50,000 lbs. Spring Single Point Suspension (Tandem)<br/>           Suspension Hanger: 21" Fabricated I-Beam<br/>           (2) 25,000 lbs. 5" Round Axles<br/>           Brake Control: Spring Loaded 16" x7.5"<br/>           ABS: 2S1M<br/>           10 Hole Uni-Mount Hubs &amp; Drums<br/>           10 Hole Uni-Mount Rims w/11R22.5 Tires<br/>           Fenders- Rubber 2-Ply<br/>           Ace Logo Rubber Mud Flap with Hook<br/>           2-Speed Landing Gear 120K lbs.</p> <p>LIGHTING &amp; SAFETY<br/>           All L.E.D Lights<br/>           All Lights Meet DOT #108<br/>           Lights &amp; Harness- Truck Lite<br/>           Body Hoist Up Alarm- LED Strobe<br/>           ICC REGULATED BUMPER- AIR ACTUATED<br/>           Meets FMCSA 49 CFR § 393.86<br/>           (4) Nylon Tie Down Strap – More can be added*</p> <p>PAINT<br/>           Cleaned, Primed, Painted Industrial Epoxy (Black)<br/>           WARRANTY- In Years<br/>           (5) On Main Frame – Excluded Rollers and Greaseable Items<br/>           (1) All Hydraulic Components<br/>           (1) on All Items Manufactured by Ace<br/>           Axles &amp; Suspension are subject to manufacturer discretion<br/>           Part: ART-60-32</p> |



| Quantity | Description   |
|----------|---|
| 1<br>/ea | RR Roll-Off Complete 32' Hyd<br>Roll Rite Tarping System (Hydraulic) - Hydraulic Ace Tower<br>Part: 654-3001-32 |
| 1<br>/ea | Ridewell 20k Air Lift Axle<br>(Non-Steerable) -11R22.5 Tire & 10-Hole Uni-mount Rim (Single)<br>Part: RCA-215T  |
| 1<br>/ea | Automatic Tire Inflation Kit  |
| 1<br>/ea | Front Work Lights - Installed<br>Part: 115-1003-I   |
| 1<br>/ea | Steel Tool Box 18"x18"x36" BIK<br>TOOLBOX,36X18X18,SST T-HDL, BLACK POWDER COATED STEEL<br>Part: 44-1003        |
|          |   |

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.  
Equipment availability, prices and specifications are subject to change without notice.