

HALE

TRAILER

BRAKE & WHEEL

Hale Trailer Brake & Wheel

A012833

VIN: 941004



Quantity	Description
1 /ea	<p>PO Line: 002 Ace ART-60-32 Roll Off Trailer NEW ACE ROLL OFF TRAILER - ART-60-32 Overall Length: 33' 6" Container Frame Length: 32' Kingpin to Last Axle: 26' 7" Rated 60,000 lbs. Lift Capacity Container Size Range- 10'-32' Outside Rail Containers</p> <p>MAIN FRAME: 12"X 4"X 1/4" Rectangular Tubing 12"X 4" Cross Members for Main Frame Top Wrap: 1/2" X 4" Flat Bar Wear Pad Bottom Wrap: 3/4" x 4" Flat Bar 1/4" Hollow Truss Mounted Below Main Frame with 1/2" X4" Bottom Wrap (2) 1 1/4" Fixed Stops at Front of Trailer (12) 3 1/2" Rollers Welded to Outside Frame 3/4" King Pin Plate with 3/4" Plate Supports & 2" Round Bar Stiffener</p> <p>STABILIZER FRAME: 4"X4"X 1/4" Tube with 4"x4"x3/8" Angle Wrap Hinges: 2" Round Bar 28"x16"x5/8" Draft Arm Support Plates</p> <p>HYDRAULICS: (2) 8.5"- 4 Stage Telescopic Main Lift Cylinder 133,000 lbs. @ 2,400 PSI (2) Ace Independent Reeves: 3 1/2" Rod 7" Bore Reeving Cylinder 88,000 lbs. ea. Directional Valve with Pressure Gauges and Adjustable PSI – Set to 2,450 PSI Hoses: 3/4" 3000 PSI Hoses with Nylon Covering Hydraulic Pipes: 3/4" Steel Pipe Standard JIC Fitting on All Hydraulics NO HYDRAULICS IN REAR OF TRAILER</p> <p>CABLE AND AFFILIATED COMPONENTS:</p>



Quantity	Description
	<p>Cable-7/8" IWRC Cable, (4) Cable Clamps, Cable Button with Cast Ring Pulleys: 10" Sheave with 2.5" Pin (Qty 3) Pulley Block - Independent (2) Independent Pulley Track</p> <p>RUNNING GEAR: H900 50,000 lbs. Spring Single Point Suspension (Tandem) Suspension Hanger: 21" Fabricated I-Beam (2) 25,000 lbs. 5" Round Axles Brake Control: Spring Loaded 16" x7.5" ABS: 2S1M 10 Hole Uni-Mount Hubs & Drums 10 Hole Uni-Mount Rims w/11R22.5 Tires Fenders- Rubber 2-Ply Ace Logo Rubber Mud Flap with Hook 2-Speed Landing Gear 120K lbs.</p> <p>LIGHTING & SAFETY All L.E.D Lights All Lights Meet DOT #108 Lights & Harness- Truck Lite Body Hoist Up Alarm- LED Strobe ICC REGULATED BUMPER- AIR ACTUATED Meets FMCSA 49 CFR § 393.86 (4) Nylon Tie Down Strap – More can be added*</p> <p>PAINT Cleaned, Primed, Painted Industrial Epoxy (Black) WARRANTY- In Years (5) On Main Frame – Excluded Rollers and Greaseable Items (1) All Hydraulic Components (1) on All Items Manufactured by Ace Axles & Suspension are subject to manufacturer discretion Part: ART-60-32</p>



Quantity	Description
1 /ea	RR Roll-Off Complete 32' Hyd Roll Rite Tarping System (Hydraulic) - Hydraulic Ace Tower Part: 654-3001-32
1 /ea	PO Line: 004 Ridewell 20k Air Lift Axle (Non-Steerable) -11R22.5 Tire & 10-Hole Uni-mount Rim (Single) Part: RCA-215T
1 /ea	PO Line: 005 Automatic Tire Inflation Kit Part: 221-1007
1 /ea	PO Line: 006 Front Work Lights - Installed Part: 115-1003-I
1 /ea	PO Line: 007 Steel Tool Box 18"x18"x36" BIK TOOLBOX,36X18X18,SST T-HDL, BLACK POWDER COATED STEEL Part: 44-1003

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.