



## Hale Trailer Brake & Wheel

A012905

VIN: 42455

### Talbert Manufacturing, Inc.

Model: T2-35CC-HRG-T1

Capacity in tons: 35

#### 1. GOOSENECK

Gooseneck design  
Loaded 5th wheel height  
Swing radius  
Support cylinder  
Power source  
Gooseneck locks  
Electrical receptacle  
Coverplate  
Additional gooseneck specifications

Ratchet  
51"  
90"  
Hydraulically operated with 4" x 3" cylinder mount cross member  
Hydraulic couplings: 3/4" fixed at front of gooseneck  
Ratchet  
Seven pin connector  
Aluminum  
1) Full penetration weld on gooseneck gusset  
2) Base pivot tube reinforcement

#### 2. DECK

Deck section design  
Deck section length  
Deck section width  
Loaded road clearance  
Loaded deck height  
Flooring  
Gooseneck/deck connection  
Deck/rear bridge connection  
Outriggers  
Slope front of deck top down  
Heavy duty front folding ramps  
Expanded metal  
Additional deck specifications

Four beam  
24'-0" (23'-6" clear)  
8'-6"  
6"  
22"  
1-1/2" apitong secured with deck screws; no lumber between main beams  
Horizontal pin and plate with remote lock  
Fixed/welded  
12" swinging/removable with double hook-on at front of deck  
With smooth plate & traction bars  
32" wood filled  
Between main beams 1st deck section at front  
None

#### 3. REAR BRIDGE

Rear bridge section width  
Loaded rear bridge height  
Number of axles  
Axle spacing  
Axle capacity  
Brakes  
Anti-lock brake system  
Wheels

8'-6"  
40"  
2  
54"  
25,000# - GAWR 20,280#  
16-1/2" x 7" air actuated with spring brakes on one axle  
Two (2) sensor, one (1) modulator system  
Ten (10) stud; 285.75mm BC aluminum/steel disc hub piloted system with oil seals, inner wheels steel with outer aluminum wheels Dura-Bright  
Eight (8) 255/70R22.5 (H) 16PR radials  
Ridewell air  
Manual  
Talbert +3", -3" with over ride chains on all axles  
Boom well, cross members recessed - recess 1st member additionally  
With chain slots and flag holder slots

Tires  
Suspension  
Exhaust Valve  
Manual raising & lowering (+3"/-3")  
Rear Bridge Center Section  
Wide center bolster

Rear half bolster	Rear of axle 2
Front bridge ramp	Sloped to deck outboard of main beams with smooth plate and traction bars
Fenders	1/4" floor plate over tires only
Additional rear bridge specifications	None
<b>4. GENERAL</b>	
Lights and wiring	12 volt system with the following: All lights to be LED including mid-turn, excluding license plate light 3 marker lights each side of deck including mid-turn Strobe lights and switch at rear Battery back-up system with switch at rear to flash all marker/tail lights and strobe lights, battery mounted in battery box.
Paint	Valspar standard Talbert black
Lash rings	12 total - 4 each side of deck (bent style), 8 total 1 each bolster and half bolster end (straight style), 4 total
Estimated empty weight	15,550#
Additional general specifications	None

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.  
Equipment availability, prices and specifications are subject to change without notice.