



## Hale Trailer Brake & Wheel

A012909

VIN: 42456

### Talbert Manufacturing, Inc.

Model: T2-35CC-HRG-T1

Capacity in tons: 35

#### 1. GOOSENECK

Gooseneck design	Ratchet
Loaded 5th wheel height	51"
Swing radius	90"
Support cylinder	Hydraulically operated with 4" x 3" cylinder mount cross member
Power source	Hydraulic couplings: 3/4" fixed at front with piping for wet line
Gooseneck locks	Ratchet
Electrical receptacle	Seven pin connector
Coverplate	Aluminum
Additional gooseneck specifications	1) Full penetration weld on gooseneck gusset 2) Base pivot tube reinforcement

#### 2. DECK

Deck section design	Four beam
Deck section length	24'-0" (23'-6" clear)
Deck section width	8'-6"
Loaded road clearance	6"
Loaded deck height	22"
Flooring	1-1/2" apitong secured with deck screws; no lumber between mainbeams
Gooseneck/deck connection	Horizontal pin and plate with remote lock
Deck/rear bridge connection	Fixed/welded
Outriggers	12" swinging/removable with double hook-on at front of deck
Reinforced top flange of sidemember	None
Slope front of deck top down	With smoothplate & traction bars
Heavy duty front folding ramps	32" wood filled
Expanded metal	Between mainbeams 1st deck section at front
Additional deck specifications	None

#### 3. REAR BRIDGE

Rear bridge section width	8'-6"
Loaded rear bridge height	36"
Number of axles	2
Axle spacing	54"
Axle capacity	25,000# GAWR = 20,280#
Brakes	16-1/2" x 7" air actuated with spring brakes on one axle
Anti-lock brake system	Two (2) sensor, one (1) modulator system
Wheels	Ten (10) stud; 285.75mm B.C. aluminum/steel disc hub piloted system with oil seals, inner wheels steel with outer aluminum wheels Dura-Bright
Tires	Eight (8) 255/70R22.5 (H) 16PR radials

Suspension  
Exhaust Valve  
Manual raising & lowering (+3"/-3")  
Suspension options  
Rear Bridge Center Section  
Wide center bolster  
Rear half bolster  
Front bridge ramp  
Fenders  
Connections for future removable axle  
Additional rear bridge specifications

#### 4. GENERAL

Lights and wiring

Paint  
Lash rings

Estimated empty weight  
Additional general specifications

Ridewell air  
Manual  
New style +3", -3" with override chains on all axles  
None  
Boom well, cross members recessed - recess 1st member additionally  
With chain slots and flagholder slots  
Rear of axle 2  
Sloped to deck outboard of mainbeams with smoothplate and traction bars  
None  
None  
None

12 volt system with the following:

All lights to be L.E.D. including mid-turn, excluding license plate light  
3 marker lights each side of deck including mid-turn  
strobe lights and switch at rear

Battery back-up system with switch at rear to flash all marker/tail lights and strobe lights, battery mounted in battery box.

Standard Talbert black, R-Cure 800 series paint

8 Total

4 each side of deck (bent style), 8 total

14,580#

None

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.  
Equipment availability, prices and specifications are subject to change without notice.