

LIVE BOTTOM	TRLLIVE	Qty
MODEL	LBW-232	
BODY CONSTRUCTION:		1
CAPACITY	33 CUBIC YARDS	1
LENGTH	32'	1
SIDES	ABRASION RESISTANT STEEL, 1/8" HARD OX STEEL	1
INSULATION	COVERED WITH SMOOTH .040 ALUMINUM,	1
ALUMINUM BIN EXTENSION	12"	1
SIDE STIFFENERS	12 GAUGE "J" CHANNELS	1
FRAME	TUBE TRUSS DESIGN W/WINGS, ONE CROSS TUBE BRACING @ REAR	1
CROSSMEMBERS	10 GAUGE	1
PRODUCT DOORS	TWIN DOORS WITH INDIVIDUAL AIR CYLINDERS (AIR CONTROL VALVE INCLUDES MANUAL OVERRIDE).	1
LIGHTS	L.E.D. TYPE, 12 VOLT SEALED SYSTEM	1
PAINT	GLOSS BLACK (2-PART URETHANE)	1
REAR FENDERS	ALUMINUM FLOORPLATE	1
FRONT FENDERS	ALUMINUM DIAMOND PLATE	A1 1
HYDRAULICS AND PRODUCT BELT:		1
PLANETARY GEAR	DOUBLE REDUCTION, 30:1 RATIO, 100,000 IN. LBS. TORQUE	1
HYDRAULIC MOTOR	15.2 C.I.D.	1
CHAIN	(8) STEEL PINTLE CHAINS, 12,500 LB. RATED	1
LADDER	MOUNTED ON ROADSIDE FOLDING	1
CHAIN ADJUSTMENT	INDEPENDENT TENSIONING MECHANISM	1
CHAIN GUIDANCE SYSTEM	ULTRA-HIGH MOLECULAR POLYETHELENE TO REDUCE FRICTION AND WEAR	1
PRODUCT BELT	42" WIDE, CHEMICAL AND HEAT RESISTANT, CONTINUOUS-NO SLATS (TEFLON BOTTOM EDGE)	1
BELT ADJUSTMENT	INDEPENDENT ADJUSTMENT AND TENSIONING MECHANISM	1
BELT RETAINER	"V" STYLE BELT CENTERING FOR POSITIVE ALIGNMENT	1
BELT FLASHING	UHMW CLAMP STYLE RETAINER	1
CHASSIS:		1
LANDING GEAR	PIN TYPE	1

SUSPENSION	AIR RIDE TANDEM (NO MANUAL EXHAUST DUMP VALVE)		1
AXLES	23,000 LB. BEAM RATING WITH HP BEARINGS.		2
AIR BRAKES	16.5" X 7" W/SPRING BRAKE AND AUTO SLACK ADJUSTERS		1
OIL SEALS	STEMCO		1
HUBS	10-STUD, HUB PILOTED		1
DRUMS	CAST		1
ALUMINUM WHEELS (POLISHED OUTERS) &	STEEL DISC INNERS		1
TIRES	(8) 11R22.5-G GENERAL HT		2
MISCELLANEOUS:			1
TARP	SHURCO ELECTRIC FRONT TO REAR W/ MANUAL OVERRIDE,	A18	1
STROBE LIGHTS	AT REAR (SET OF 2)		1
WORK LIGHTS	AT REAR (SET OF 2)		1
HYDRAULIC JUMPER HOSES	TRAILER TO TRACTOR		1
BACKUP ALARM	ELECTRIC	A12	1
RELEASE AGENT SYSTEM	AIR PRESSURIZED W/TANK, HOSE REEL, 25' HOSE & WAND (MOUNTED NEXT TO CENTER LADDER (REARWARD)		1