

# HALE

## TRAILER

### BRAKE & WHEEL



**Resale Inventory**  
**A013364**  
**VIN: 180001**

#### SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b>	800-383-8894	<b>Jacksonville, FL:</b>	800-828-3055
<b>Baltimore, MD:</b>	888-601-7500	<b>Little Rock, AR:</b>	833-424-8944
<b>Boston, MA:</b>	800-854-5310	<b>Portland, ME:</b>	800-325-4253
<b>Concord, NC:</b>	800-438-2250	<b>Richmond, VA:</b>	866-839-3495
<b>Delmar, DE:</b>	866-486-1400	<b>Scranton, PA:</b>	800-569-1400
<b>Des Moines, IA:</b>	888-673-5011	<b>Springfield, MA:</b>	800-854-5306
<b>Elkton, MD:</b>	800-544-7127	<b>Voorhees, NJ:</b>	866-315-0235

HaleTrailer.com | @haletrailer   
**800-232-6535** \*FINANCING AVAILABLE

#### GVWR

GVWR:	Trailer to meet 68,000 Pound GVWR
VIN PLATE:	US - VIN Plate to Read in English (Standard)
* Product Type:	HT HyCube

#### GEOMETRY

Length - Exterior:	53'-0"
** Length - Interior:	52'-6" Nominal Lining To Lining
Width - Exterior:	102.36"
** Width - Interior:	101" Nominal Lining To Lining
Height - Exterior:	13'-6"
** Height - Interior:	110" Nominal
Deck Height:	Standard application
Fifth Wheel Height:	47"
King Pin Location:	36"
Landing Gear Location:	107" from King Pin (+ 1"/-0")

#### TIRES & WHEELS

Tire Furnished:	Factory Furnished
* Tire Manufacturer:	Hankook TL01(G), Low Rolling Resistance Tire
Tire Size:	295/75R22.5
Wheel Furnish:	Factory Furnished
Wheel Material:	All Steel Wheel
Wheel Manufacturer:	HT Standard (TCC 361)
Wheel Size:	8.25 x 22.5, 5-Hand Hole (Steel, Inner & Outer)
Wheel Finish for Steel:	Powder Coated White Steel Disc
Wheel Finish for Aluminum:	None (Due to All Steel Wheel Application)
Valve Stem & Cap:	Valve Stem & Metal Dome Cap

#### UPPER COUPLER

Approach Plate:	1/4" thick 80,000 Lb Yield - 6 Support Channels
King Pin (BTM Main) Plate:	1/4" thick 80,000 Lb Yield
King Pin & Manufacturer:	Standard (Jost) AAR Cruciform King Pin
* Front Bottom Rail:	Stainless Steel, w/ Pick-Up plate Striker Angle
Upper Coupler Tube Qt'y:	(1) Tubing Application - Joggled

#### BODY/BASE

Forward Crossmember:	Steel Hat Shaped Upper Coupler to Landing Gear : 12" C/L
Landing Gear Crossmember:	4" Steel I-Beams (80,000 PSI) : 12" C/L (5ea)
Bay Area Crossmember:	4" Steel I-Beams (80,000 PSI) : 12" C/L
Running Gear C/M Size:	4" High
Running Gear Crossmember:	4" Steel I-Beams (80,000 PSI) : 12" C/L with 8" C/L Last 3.4'
Slider Body Rail (VT):	208" Rail Length

#### FLOOR

Upper Coupler Type:	3.40" Joggled with Exposed Coupler Top Plate (New STD)
Floor Specification:	1.38" (1-3/8") Nominal Domestic Laminated Oak Hardwood
Floor Ratings - VT:	18,000 lbs Rated Floor per TTMA- Standard HT Dry Van Floor Rating
Floor- Assembly Method:	Wood Floor Assembly

Floor Screws: (3) 0.31" Dia. screws per Board on I beams  
\* Threshold-Finish: Hot Dip Galvanized  
Threshold Plate: 0.13" X 12" Deep Steel Diamond Plate w/ Screws and Nuts  
Threshold-Application: Standard Application

**FRONT**

\* Front Corner Radius: 4" Aluminum Cover Sheet  
Front Panel & Color - Dry: 0.05" Aluminum Prepainted White w/ natural color rivets  
\* Front Corner Mat'l - Dry: 0.05" Aluminum Prepainted White  
Front Posts: (4) 2.5" Deep (16GA) Steel Hats Welded to Upper Coupler - Non AAR  
Gladhands: Phillips Qwik-E with Filters Control Line Only. Overlaid  
Front Receptacle(7-Way): Phillips 7-Way without Circuit Breakers, Split Pins with QCS plug  
Front Receptacle(7-Way) - Options: Phillips QCS Plug connector  
Gladhand/7-Way Location: Overlaid on Lower Roadside Front  
\* Corner Radius Protector: (2) 0.125" X 12" Alum Diamond Plate Each Side at Top

**SIDE**

\* Side Material: 0.05" Aluminum Prepainted White w/ natural color rivets  
\* Side Posts: 0.45" Deep 14 Gauge Galv Steel "A" Slotted Logisitic Posts  
\* Side Post Centers: 16" C/L with 12" C/L @ Upper Coupler and Support Gear  
\* Side Top Rail: Shallow Post Side Top Rail  
\* Side Bottom Rail: Side Bottom Rail STD  
Fasteners to Bottom Rail: Standard Rivets to attach C/Members to the Side Bottom Rail

**REAR**

Rear Frame: Swing Door, 2" Shallow Header (with 1 Lock Rod Per LH & RH Door)  
Rear Door Opening Spec.: Standard Application  
Floor Level: Door to be Flush with Floor (STD)  
Door Type for Dry Van - SW: 0.5" Xxentria Composite Swing Door. Galvanized Prepainted White Interior & Exterior Skin  
\* Option - Door (Main Line): Install Standard Anti-Theft Hardware  
Option - Door Install Instruct: Standard Door Installation per Manufacturer's Recommendation  
Option - Door & Hardware: One(1) Rubber Door Bumper Standard (1" Deep) on Hinge of each Swing Door  
Hinges: Four (4) Aluminum Hinges per Door  
\* Additional Hinge Option: Additional One(1) Aluminum Hinge (Total 5 Per Door)  
Rear Underride Guard: 4" Tube Bolt on Assembly w/ Welded Perforated(Pooched) Horizontal  
Option - Horiz Member/Other: Construction of two pieces standard stitch welding  
Underide Bolt Spec.: Zinc plated bolts & nuts - Standard  
Dock Bumper: Pair 2" X 4" Mold Bolted Bumper  
Rubber Bumper Location: Inboard of Light Protector Bars (Standard)

**LIFT GATE**

**ROOF**

Roof Panel: 0.040" Aluminum  
Roof Bow: 16 Gauge Galvanized Steel Anti-Snag  
Roof Bow Centers: 24" Centers Full Length

**LINING/SCUFF**

\* Side Lining: 0.235" HDPE Recycled Plastic Installed between Posts  
Front Lining: 0.25" Top and 0.5" Bottom plywood Mounted to Front Posts Full Height  
\* Base Side Scuff: 0.63" x 12" High White Recycled Plastic  
\* Mounting Method: Mounted Directly to Posts  
\* Front Scuff: 0.63" x 12" High White Recycled Plastic Mounted Over Lining to Front Posts (Overlaid)  
Corner Finish/Treatment: Standard Application

**LANDING GEAR**

L/Gear Spec.: Jost HT421.G3.17.157 5 Year Warranty Full HDG  
L/Gear Mt'g Method: Inboard Mounting (Standard)  
L/Gear Shoes: 10" X 10" RCF (Removable Cushion Foot) Low Profile

L/Gear Ground Clearance:	Nom. 12" Ground Clearance
L/Gear Mt'g Bracket:	Hot Dip Galvanized Large Wing Plate
L/Gear Crank Handle:	Roadside
L/Gear Options:	None (HT STD)
L/Gear Cross Brace Design:	HT Standard Cross Brace attachment Design

**RUNNING GEAR**

Bogie Type:	Sliding Tandem(2) Axle Bogie
Axle Spacing:	49" Axle Spacing
Axle ABS System:	Tandem Axle w/2S1M ABS System
Bogie & Axle Location:	Location to be Sliding Tandem Axle for specified slider Length w/Stop Bars @ Front & Rear
Option-Related Bogie Stopper Feature:	STD plug stopper
Susp. Manufacturer:	Hendrickson
Suspension Capacity:	Standard Duty
Susp. Specification:	Hendrickson Vantraxx HKANT40K Air Ride
Surelok (Anti-Dock):	Surelok (Anti-Dock) Installed
Locking Pin Mechanism:	Air-Assist Pin Puller or Quik Draw
Susp. Sub-Frame:	Hendrickson K-2 STD Duty
Type of Susp Spring:	Air Bag
Spring Specification:	Air Bag
Axle Supplier:	Hendrickson
Axle-General Spec.:	Axle - Tandem (2) Axle included in Suspension (For 2S1M or 2S2M System)
Axle-Track Length:	77-1/2"
Axle-Spindle Type:	Tapered Spindle
Brake Lining Size:	16.5" X 7"
Brake Lining Spec.:	Hendrickson Extended Service (Abex-3030-197)
Brake Control System:	2S/1M Wabco ABS
Spring Brake Control:	Sealco 110500 Springbrake Priority
Brake Cont-Hose & etc.:	Standard Air Line & Hose Application (US&Canada)
Slack Adjuster Spec.:	Gunitite Auto-5.5", 28 Spline
Brake Chamber Spec.:	TSE 3030 Tamper Resist (HT standard)
Stroke Length:	MFG's Standard Stroke Length
Hub Specification:	HT Standard (KIC) 10 Stud Hub Piloted Outboard Iron Hub
Drum Specification:	HT Standard (KIC) Cast Drum
Hub/Drum-Opt(Nut&Other):	Standard
Bearing Specification:	Stemco
* Lubrication Spec.:	Chev Delo (Syn) Grease
* Wheel Seals Spec.:	Stemco Discover Seals, Hub Cap included in tire inflation system, Pro-Torq Nut
* Hubodometer:	Stemco Hubodometer, Bracket Mounted, Reading in Miles
* Hubodometer Location:	Roadside (LH) Front Axle
* Tire Inflation Spec.:	Hendrickson Tire Maax Inflation System for Undressed Axle (This kit include Hendrickson Hub Cap for TireMaax)
Tire Inflation Pressure:	100 PSI
* Tire Inflation Lamp Location:	Indicator PSI Light at Roadside Mounted over corner radius. (STD location)
* Tire Inflation Lamp Spec.:	19 Series Lamp

**ELECTRICAL**

Harness-General Spec.:	Molded Color Code Phillips Harness with QCS Plug
Harness-Special Feature:	Manufacturer's Standard Feature
* Front Light:	(2) Trucklite 33275Y LED PC Rated Mounted with Grommet
* Rear ID Header Light:	(5) Vision CL11120R3 LED PC Mounted with Grommet (Dual Function)
* Rear ID-Special Feature:	Dual Function Rear Header Lights - 3 Lamps at center with Marker & Stop functionality, 2 Lamps outboard with Marker & Turn functionality
Rear Side Marker Type(Shape):	Mini Button Style Lamp
* Rear Side Marker Detail Spec:	(2) Trucklite 33275R LED PC Rated Flush w/ Grommet 33725 w/ anti-theft hardware

Rear Side Marker MT'G Location: Mounted on Standard Location on Rear Corner Post - HT STD

\* S/T/Tail Light-Quantity & Type: (4) Trucklite 40 or 44 Series (Round Style) or Equivalent

\* S/T/Tail Light-Detail Spec: (4) Trucklite 44322R LED (Super 44 Grey) Flange Mounted w/ Stainless Steel Rivets

Main Mid-Turn Light: Install the Mid turn lamp

\* Main Mid-Turn Light-Detail Spec: (2) Trucklite 60272Y LED Gray Flange Mounted with Stainless Steel Rivets

ABS Light Type(Shape): Mini Button Style Lamp

\* ABS Light Detail Spec: (1) Trucklite 33275Y LED PC Rated w/ Grommet 33725 w/ anti-theft hardware

ABS Light MT'G Location: Mounted on Standard Location on Rear Corner Post - HT STD

\* License Light: (1) Trucklite 33010C LED

Option Related Harness/Wiring: Standard

Electrical Related Regulation: Standard Application

**MARKING/DECALS**

HT & Product Type Decal Package: Hyundai Logo & Product Type Decals Application(For not having pre-painted white panels for side/door/front, Apply white HT Corporate decals)

Decal Package: Factory Furnished Hyundai Information & Regulatory Decal Package with FMCSA Specified in Notes

Decal Opt 2-Decal Location: Standard Application

Decal Opt 3-Decal Installation: Standard Application

Conspicuity Markings: Hyundai Standard Conspicuity with Logo Applied to Side Bottom Rail

License Plate: Temporary For Delivery. Fasten On HDG Mounting Plate

License Plate Brk't Install: Standard Install Location - Roadside Below Sill Pane

\* Do not use...Registration/Manifest Box: DO NOT USE, USE VRF05...(1) Factory Choice-Trucklite 97960 or Phillips 16-802

Furnish Document Holder: Factory Furnished

Document Holder Detail Spec.: (1) Phillips 16-802

Document Holder/Manifest Loc.: Overlaid on Lower R/S Front

**PAIN/FINISH**

\* Upper Coupler Finish: Stainless Steel-Forward Section w/ Black Undercoating inside of Upper Coupler

\* Crossmembers Finish: HDG : Slider(Bogie) crossmembers w/slider rail, Others-Prime and Black Undercoating

\* Axle & Components Finish: Black Undercoating

\* Susp. Sub-Frame Finish: Black Undercoating

L/Gear(K-Bracing) Finish: Hot Dip Galvanized

\* L/Gear(Upper Leg) Finish: Hot Dip Galvanized

Rear Frame-Finish: Hot Dip Galvanized

Rear Frame-Paint Color: None (For Galvanized or Stainless Steel)

Rear Underride-Finish & Spec.: Hot Dip Galvanized & Welded Horizontal Member

Rear Underride-Paint Color: None (For Galvanized or Stainless Steel)

**MISCELLANEOUS**

Mudflap Provider: Factory Furnished Mudflaps

Mudflap Specification: 24"x30" White Plain Plastic with Hyundai Logo

Mudflap Mounting Loc.: Suspension Frame

Mudflap Mounting: STD Location w/ H.D Washer Retainer

\* Lift Pad Spec.: Install HT Occasional use lift pads for delivery, with HYUZ decals

**DISCLAIMER**

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.