

HALE

TRAILER

BRAKE & WHEEL



Resale Inventory

A014515

VIN: 578043

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

Magnitude 55LCC Air Tridem (Flat Low Deck) (Model: MAG55L)	
	Est. Wt.: 22,760# +/- 3%
Capacity: 55 tons in 13-foot length with 4 axles close coupled; - GAWR and tire ratings determine legal payloads	
Load Base: 13-foot rigid 2-point load centered in deck area with 4 axles close coupled	
Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs	
Compatibility: Designed to accept 55/60 rear axle below	
Gooseneck Design: Hydraulic removable non-ground bearing design	
Loaded Fifth Wheel Height: Dual Cam Pawl Arm Assembly with 7 ride height positions (50 inches nominal)	
Swing Radius: 108 inches (12 feet 7 inches overall gooseneck length)	
Kingpin: Removable kingpin at 108 inch radius	
Alternate Kingpin: Alternate Kinpin location at 89 inch radius	
Power Source: Set up for wet line operation	
Electrical Receptacle: J560 7-pin connector	
Deck Width: 8 feet 6 inches overall (unless optional deck width is selected)	
Deck Length: Flat Level Deck (FLD) design - standard 26 feet clear deck length	
Loaded Deck Height: 18 inches with 6 inches ground clearance	
Flooring: 2 inch nominal wood - side rails only	
Front Ramps: Manual front approach ramps included	
Front Bogie Ramp: Included as standard	
Extension Brackets: 13 pair - 26 total removable swing type, 2 pair - 4 total heavy duty removable hook-on type (26 swing type, 4 hook-on type on 27 foot deck)	
Deck to Bogie Connection: Fixed	
Tool Box: 2 Fully covered trays in front of deck between mainbeams with lockable covers.	
Crossmembers: Recess last 3 crossmembers in deck	
Hammer Plate: Hammer Plate (16in x 60in x 1/2 in) installed over recessed crossmembers. Preforated plate under hammer plate	
Number of Axles: 3 axles	
Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
Axle Spread: 54.5 inches (between axles)	
Dust Shields: None	
Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
Suspension: Air ride	
First Axle Lift: None	
Third Axle Lift: Air lift	
Tires: 275/70R 22.5 OEM standard	
Wheels: 8.25 x 22.5 Lvl one buffed outside/steel disc - hub-piloted inside	
Bolsters: Recessed load bearing between all axles and rear of last axle	
Covered Rear Bogie: None	
Rear Bogie Height: 40 7/8 inches to top flange - 36 5/8 inches to top of bolsters	
Boom Trough: V-style boom trough with bolt-in V pan	
Mechanical Ride Height Control: Mechanical ride height control valve (Whittle Style)	
Manual Dump Valve: Installed	
Bumper: Heavy duty V-style rear bumper	
Width: 8 feet 6 inches	
Flip Axle: None standard	
Dust Shields on Flip Axle: None standard	

Electrical System: DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes	
Paint: Fontaine standard Red polyurethane enamel	
Lash Rings: 19 pair - 38 total	
Flag Holders: Flag holders - 1 pair located at front of deck and on rear bumper	
Accent Package: None	
Liquid Filled Gauge: None	
VIN Plate: Bilingual VIN plate	
Registration/Document Holder: Install registration/document holder	
Please Note: Price includes commodity surcharges	

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.