

Model: AC-20-AR Capacity in tons: 20

1. TONGUE

Pintle eye Tongue

Drop leg

Electrical receptacle Headboard **2. DECK** Deck section design

Deck section length Deck section width Loaded deck height Flooring Lash rings

Crossmembers Mainbeams Sidemembers Beavertail Ramps **3. RUNNING GEAR** Number of axles Axle capacity Brakes Wheels

Suspension 4. GENERAL Lights and wiring

Tires

Paint Estimated empty weight Additional general specifications Talbert ® SINCE 1938

Adjustable pintle eye (3" ID) with 48" chain and grab hooks 5'-6" with lockable tool box with aluminum diamond plate lid - move hinge 4" forward 2-speed, 50,000# crank down dual landing leg, mounted to main beams and headboard Seven pin connector 8" high full width One piece tongue, main beam and beavertail (cold formed) 27'-0" (21'-0" flat with 6'-0" beavertail) 8'-6" 32-1/4" 1-1/2" apitong with individual wheel wells 10 total -4 each side on flat deck (straight style), 8 total 1 each side on beavertail (straight style), 2 total 6" deep hi-tensile 12" deep hi-tensile 8" deep hi-tensile 6'-0" Double break with wood flooring full width 38" wide x 6'-6" long air ramps with wood flooring, stored vertically with lock bar 2

25,000#, full width track 12-1/4" x 7-1/2" air with 2S/1M ABS. Spring brakes on both axles. Steel disc with oil seals (6.75 x 17.5) Eight (8) 215/75R17.5 (H) 16PR radials

Use valve stem extensions on inside wheels 44,800# Hutch spring

12 volt LED system (license plate regular), supplied with female 7-way plug on tongue, SUPPLY JUMPER CORD FOR TRUCK Valspar standard Talbert black 9,140# Formed step in front of 1st axle both sides of trailer

DISCLAIMER