



Qty Overall Width = 96" Overall Height= 12' 0 " (w/ 48" fifth wheel) Capacity = 1033 cubic feet

3-Hopper, 45 Degree Vessel 5' Product Valves Toerails on Vessel (extending to frontmost manhole) Soft Coated Suspensions P Spindle Axles Stemco Platinum Plus Wheel ends 5-yr./500,000-mi. Aluminum Fenders (Front & Rear) Aluminum Air Tank LED Lights

\*\*\* NOTE: It is recommended that the interior of the vessel be cleaned professionally prior to initial loading to avoid product contamination.

<u>Quantity</u>		Cat	egory	Description		
Base Trailer 10611-APB 1033-Base						
1	10611	Materials Hauling	APB1033 1033 Cu. Ft. Pneum	natic Dry Bulk Trailer		
1	10612	Fifth Wheel / King	Standard Fifth Wheel (Bolted	I & Adjustable)		
1	12882	Body	Standard Length & Vessel Lo KP to center of vessel)	ocation (37'-11" KP to last axle; 220"		
1	10614	Frame	Aluminum End Frames			
1	10616	Struts	Aluminum Struts			

1 1 1	10618 10621 10624	Vessel Vessel Vessel	Standard Length & Vessel Location (37'-11" KP to last axle; 220" KP to center of vessel) Non Food Grade w/ Standard Finish 2 Manholes - 20" Manholes w/ Nylon Wear Plate (Center & Rear)
1	10627	Inlet Piping	3" Air Inlet on Road Side w/ Male Adaptor
1	10629	Blow Down Line	Road Side Front, Terminating Between Mainframe, Angled Towards Rear
1	10632	Top Air Line	Top Air w/ Check Valve (Road Side Front)
1	10634	Aeration	3 Solimar Fluidizers Each Hopper W/ Hopper Savers (Controlled by One (1) 3" Butterfly Valve on Front Fender)
1	10637	Product Line	5" Ultraflo #400 (Iron Disc W/ Black Nitrile Seat)
1	10639	Tees	5" x 4" Aluminum Gravity Drop
1	10646	Product Line	4" Sch 40 Aluminum W/ Grooved Pipe Connectors
1 1	10653 10658	Discharge Piping Discharge Piping	4" Sch 40 Aluminum W/ Grooved Pipe Connectors Terminating Thru Axles
1	10659	Hose Tubes	8" x 21' Aluminum - Curbside
1	10666	Suspensions	Tandem Axle: (2) 23k Intraax AAT Air Ride w/ Inverted Drop Center Axle
1	10670	Brakes/ Air	4S2M Anti-Lock Brake System
2	10671	Hub/ Drum	Duralite hub-piloted - Centrifuse drum (per axle)
4	08380	Down Axle Wheels (inside)	8.25 x 22.5 10-hole machined aluminum wheel -Accuride
4	08380	Down Axle Wheels (outside)	8.25 x 22.5 10-hole machined aluminum wheel -Accuride
8	08254	Down Axle Tires	11 R22.5 Continental HSR-2 16 Ply (per tire) ILO Std Tire
1	10674	Ladder	Ladder@ Rear w/ Hand Rail
1	10675	Gauges	Gauges on Side of Frame W/ Light
1	10678	Lights / Electrical	LED Lights - DOT Required w/ Midturn (High Mounted 3rd Stop Light)
1	10672	Flaps, Mud	Trail King Anti-Sail Mudflaps
1	10663	Landing Gear	Two Speed (crank road side) (Armor Coated black)
1	08031	Paint	Grey S7230 with black decals (735-489-029)
1	80228		80228 (APB) Blow Down Line - Road Side Rear, Terminating Ahead of Rear Fender

DISCLAIMER Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.