

HALE TRAILER BRAKE & WHEEL



Resale Inventory
A017316
VIN: 061879

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

TKS0AACS-34 All Aluminum Step Deck Trailer

Overall Width: 102"
Fully Loaded Deck Height: 34" Loaded
Ground Clearance: 9"
Capacity:

2-axle: 80k Distributed
3-axle: 85k Distributed

Upper Deck Crossmembers 18" O.C .
Main Deck Crossmembers 12" O .C .
Aluminum Rub Rail w/ Chain Spools
Stake Pockets (24" O .C .) - Sides & Front
Full-Length Hook Track
Anti-corrosion Barrier Between Aluminum & Steel Zinc Coated Steel Components
Armor Coated Landing Gear
12-1/4 X 7-1/2 Brakes
Manual Raise/Lower w/ Gauge in Enclosure
Dock Bumpers
Sealed Electrical System
LED Lights

13721-AACS-34-Base Trailer

1	13721	Open Deck	TK80AACS-34 All Aluminum Step Deck Trailer
1	13736	Upper Deck	10'-6" Upper Deck Length
1	13730	Fifth Wheel / King Pin	20" Kingpin Setting (76"/82" Swing Clearance w/ 10'/10'-6" Upper Deck)
1	13732	Fifth Wheel / King Pin	48 - 50" 5th-wheel Height
1	13727	Overall Length	52'-10" Overall Length
1	13738	Main Deck	60k in 10' Concentrated Load Rating w/ 50k in 4' C oil Pack (std location)

1	13739	Decking	Aluminum Decking w/ Flush Apitong Nailers
1	13742	Tie Downs	No Sliding D-Rings on Upper Deck
2	13745	Tie Downs	Sliding Winches on Upper Deck (each)
1	13746	Tie Downs	No Sliding D-Rings on Main Deck
10	13749	Tie Downs	Sliding Winches on Main Deck (each)
1	13750	Tie Downs	Winch Track Stops: Removeable
10	13753	Tie Downs	J- Hooks (each)
1	13754	Tie Downs	No Stake Pockets on Rear
1	13757	Suspensions	Tandem Axle: (1) 23k Air Ride w/ (1) 23k Air Ride Rear Slider
1	13765	Suspensions	49" Closed / 121" Open (slider only)
1	13767	Suspensions	Suspension Set Ahead 36" w/ Underride Guard (California & Canadian Overhang Legal for 52'-10" OAL, 20" KP, & 49"/121" Slider Spacing)
1	13768	Axles	Standard Axle
1	14432	Axles	Tiremax CP Tire Inflation (2-axle)
1	13774	Brakes/ Air	2S1 M / 2S2M Anti-Lock Brake System
1	13776	Brakes/ Air	20k Drum Brakes (per axle)
1	13778	Hub/ Drum	Steel Hub-Piloted - Cast Drum (per axle)
4	08183	Wheel Finish (inside)	6.75 x 17.5 8-hole machined (SP) aluminum wheel (per wheel) ILO Std 6.75 x 17.5 8-hole steel disc wheel
4	08193	Wheel Finish (outside)	6.75 x 17.5 8-hole machined (SP) aluminum wheel (per wheel) ILO Std 6.75 x 17.5 8-hole steel disc wheel
1	10058	Spare Wheel	No spare wheel
8	13038	Tire Size	245/70R17.5 -18 ply in lieu of STD 235/75R17.5 -18 ply HTL2 (per tire)
1	10059	Spare Tires	No spare tire

1	13795	Lights / Electrical	LED Lights - DOT Required w/ 6 Extra Clearance Lights & 1 Extra Mid-turn Light Per Side (XXXXOXXOXX)
1	13796	Lights / Electrical	4" Amber Strobe Light Replacing Inner Most Tail Light w/ Switch in Box (wired to brown)
1			
1	13784	Flaps, Mud Guards & Fenders	Mudflaps: All Axles (standard TK)
1	13785	Landing Gear	Standard Two-Speed (crank road side)
1	13781	Spare Tire Carrier	No Spare Tire Carrier
1	13787	Toolbox	Toolbox: 14" x 18" x 48" Single Door -Roadside Ahead of Front Axle
1	13789	Bumper	No Non-Certified Bumper
1	13791	Flagholders	Standard Flagholders (3 per side)
1	13792	Document Holder	Document Holder: 4-1/2" Round
	13798	Decals	Decals: Standard TK (black)

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.