

# HALE TRAILER BRAKE & WHEEL



**A017431**  
**VIN: 43231**

SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b>	800-383-8894	<b>Jacksonville, FL:</b>	800-828-3055
<b>Baltimore, MD:</b>	888-601-7500	<b>Little Rock, AR:</b>	833-424-8944
<b>Boston, MA:</b>	800-854-5310	<b>Portland, ME:</b>	800-325-4253
<b>Concord, NC:</b>	800-438-2250	<b>Richmond, VA:</b>	866-839-3495
<b>Delmar, DE:</b>	866-486-1400	<b>Scranton, PA:</b>	800-569-1400
<b>Des Moines, IA:</b>	888-673-5011	<b>Springfield, MA:</b>	800-854-5306
<b>Elkton, MD:</b>	800-544-7127	<b>Voorhees, NJ:</b>	866-315-0235

HaleTrailer.com | @haletrailer

**800-232-6535** \*FINANCING AVAILABLE

**Model:** AC3-25  
**Capacity in tons:** 25

Pintle eye Tongue	Adjustable pintle eye (3" I.D.) with 48" chain and grab hooks 5'-6" with lockable tool box with aluminum diamond plate lid Note: Move tool box hinge 4" forward
Landing Gear	2-speed, 50,000# crank down dual landing leg, mounted to main beams and headboard
Electrical receptacle	Seven pin connector
Headboard	8" high full width
Deck section design	One piece tongue, main beam and beavertail (cold formed)
Deck section length	30'-0" (24'-0" flat with 6'-0" beavertail)
Deck section width	8'-6"
Loaded deck height	32-3/4"
Flooring	1-1/2" apitong with individual steel floor plate wheel covers
1 Lash rings	10 total - Located as follows, dimensions referenced from pintle eye plate and centered on a cross member: 1st lash ring 84" 2nd lash ring 150" 3rd lash ring 241" 4th lash ring 290" 5th lash ring 345"
Mainbeams	12" deep hi-tensile
Crossmembers	6" deep hi-tensile
Sidemembers	8" deep hi-tensile with lips out for outriggers
Beavertail	6'-0" with wood flooring full width
Ramps	5'-0" self cleaning with spring assist, gripper bars and grab handles
Number of axles	3
Axle capacity	25,000#
Brakes	12-1/4" x 7-1/2" air with 2S/1M ABS. Spring brakes on axle 2 & 3.
Wheels	Steel disc with oil seals (6.75 x 17.5)
Tires	Twelve (12) 215/75R17.5 (H) 16PR radials Use valve stem extensions on inside wheels
Suspension	67,200# Hutch spring
Lights and wiring	12 volt LED system (license plate regular), supplied with female 7-way plug on tongue, SUPPLY JUMPER CORD FOR TRUCK
Paint	Valspar standard Talbert red, R-Cure 800 series paint
Additional general specifications	Formed step in front of 1st axle both sides of trailer Six (6) 12" Swinging/removable outriggers each side of deck. Located as follows, dimensions referenced from pintle eye plate and centered on a cross member: 1st outrigger 199" 2nd outrigger 234" 3rd outrigger 248" 4th outrigger 283" 5th outrigger 297" 6th outrigger 332"

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.