

EAST.

A017500 VIN: 85642

## SALES | RENTALS | PARTS | SERVICE

Jacksonville, FL: 800-828-3055 Allentown, PA: 800-383-8894 Baltimore, MD: 888-601-7500 Little Rock, AR: 833-424-8944 Boston, MA: 800-854-5310 Portland, ME: 800-325-4253 Concord, NC: 800-438-2250 Richmond, VA: 866-839-3495 Delmar, DE: 866-486-1400 Scranton, PA: 800-569-1400 Des Moines, IA: Springfield, MA: 888-673-5011 800-854-5306 Elkton, MD: 800-544-7127 Voorhees, NJ: 866-315-0235

HaleTrailer.com | @haletrailer f y in @ &

**800-232-6535** \*FINANCING AVAILABLE

Length	33	ВОГ	DY SPECIFICATIONS	Body	
Width	96" INBOARD	Tarp	NONE	Accessories	
Side Height	64" SOLID	Bow Holders	NONE		
Top Rail	9" DUMP	Tarp Bows	NONE		
Side Matl-front	4'100 WALL	Tarp Basket	NONE		
-middle	23'140 WALL	Tarp Hooks	NONE		TAILGATE
-rear	6'180 WALL	Bulkhead Mat'l	3/16" (10)	Height	FULL - GENESIS
Side Options	NONE	Bulkhead	D/S-MANDOOR	Mat'l Thkness	.140 WALL
Floor Mat'l	1/4" FULL LENGTH	Options	5" SLOPE PLATES	Slope	NONE
		Body Fenders	18"	Hinges	OVERSLUNG
Crsmbr Spacing	12"	Ladders (Out)	D/S-REAR	Side Swing	YES -W / GRD CNTRL-P/S HINGE
				Gateseal	RUBBER
Floor Options	STUB LONGITUDINALS	Inside	NONE		
				Safety Latch	ONE EACH SIDE
		Shovel Hgr	INSIDE P/S OF DOGHOUSE		
Tailgate Control	AIR / FRAME + ELEC CC (4)			Coal/Grain Door	NONE
Body Pkg	NONE	Light Panel	FULL - LED; X=LED B/U LIGHTS		
Options			OOOX ooo XOOO (11)	Coal Chute	NONE
Vibrator	NONE	Marker Lights	LED 13 PR TOP & BOTM EVEN	Gate Options	
Mudflaps	STD + ACROSS REAR (1)	MMTS	SPACING -BELOW RAIL - LED		
		Apron	NONE		
			CHASSIS SPECIFICATIONS		
Model	TRIAXLE-2 FIXED-FRONT LIFT	ABS	2S/1M	Tire Carrier	NONE
Beam Mat'l	ALUMINUM			Landing Gear	2 SPEED JOST AX150
Length	34'				D/S CRANK
Width	96"	Independ. Susp(	s)	Chassis Lights	NONE
Hoist	85-265 (2)(10)				
Chassis Neck	STD			Elec Coupler	7 WAY + ISO 7 WAY LABELE
King Pin Setting	18"	Distance	):		AUXILIARY (2)
5th Whl Plate	3/8" W/ 3/8"X 3" X 7" MOUNT	From:		Hyd Tank	NONE
5th Whl Ht	50"			Hyd Hose Fitting	WINGNUT
Overhang	6"	Controls		Hyd Hose Length	108"
Rear Axle Setting	21.5"			Tow Hooks	TWO-ONE EACH SIDE
K/P To Rear Axle	411.5"			Paint	BLACK SOFTCOAT
Suspension	AAT30K / E3-2 L LIFT-E1 (3)(5)	Location			
Susp Control	FRAME + ELEC CC (4)(9)	Axle(s)			NONE
Susp Spacing	52" - 52" (6)				
Susp Options	GALVANIZED HANGERS	Accessories		Chassis	CHASSIS REAR CM: TAPERED
Springs	AIR			Options:	W/ DIAMOND PLATE COVER
Axles	TP SPINDLES	Brakes			
Accessories	NONE	Drums			
Brakes	16-1/2" x 7"	Hubs			
Drums	CAST				TIREMAXX PRO INFLATION
Hubs	10 STUD STEEL	Wheels			SYSTEM ALL AXLES
Wheels	8.25 x 24.5 12 HP	Tires			
Tires	11R 24.5 R250 ED 16PLY BS				

1. BLACK RUBBER FLAP AHEAD OF AXLE #1 IN THE CENTER. INSTALL 4" FORWARD OF STANDARD POSITION.					
2. ADD JUNCTION BOX @ INSIDE FRAME RAIL W/ 7 WIRE FROM AUXIL PLUG IN TO JUNCTION BOX					
3. RIGHT WEIGH OIL FILLED GAUGE (KG) (FLUSH) ON FRONT CHASSIS CROSSMEMBER.					
4. WIRED TO AUXILIARY ISO 7 WAY PLUG					
5. HEIGHT CONTROL VALVE ON AXLE #2.					
6. LIFT AXLE TO BE CONTROLLED THROUGH FRAME SWITCH & ELEC CC (WIRED TO AUX 7 WAY PLUG) AND TO HAVE BRAKE RELEASE (LIFT AXLE TO SPIN FREELY).					
7. ALL FRAME SWITCHES TO BE IN POLY BOX ON D/S NEAR LANDING GEAR AIR IN THE BOX	CHANGE 1	1			
8. PLASTIC INSULATORS BETWEEN WHEEL/DRUM & WHEEL/HUB ALL AXLES.					
9. INSTALL CROSSOVER KITS	WEIGHT:	14,036			
10. NO OUTSIDE ACCESS OR FLAP ON OUTSIDE OF BULKHEAD FOR HOIST-ONLY ON INSIDE DOGHOUSE.					
11. LED BACK UP LIGHTS WIRED TO AUXILIARY ISO 7 WAY PLUG					