

HALE TRAILER

BRAKE & WHEEL
GENESIS FRAME DUMP



A017594
VIN: 85636

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

Length	33	BODY SPECIFICATIONS		Body
Width	96" INBOARD	Tarp	NONE	Accessories
Side Height	64" SOLID	Bow Holders	NONE	
Top Rail	9" DUMP	Tarp Bows	NONE	
Side Mat'l-front	4' - .100 WALL	Tarp Basket	NONE	
-middle	23' - .140 WALL	Tarp Hooks	NONE	
-rear	6' - .180 WALL	Bulkhead Mat'l	3/16" (10)	TAILGATE
Side Options	NONE	Bulkhead	D/S-MANDOOR	Height
Floor Mat'l	1/4" FULL LENGTH	Options	5" SLOPE PLATES	Mat'l Thkness
Crsmbr Spacing	12"	Body Fenders	18"	Slope
		Ladders (Out)	D/S-REAR	Hinges
				Side Swing
Floor Options	STUB LONGITUDINALS	Inside	NONE	Gateseal
		Shovel Hgr	INSIDE P/S OF DOGHOUSE	Safety Latch
Tailgate Control	AIR / FRAME + ELEC CC (4)			Coal/Grain Door
Body Pkg	NONE	Light Panel	FULL - LED; X=LED B/U LIGHTS	Coal Chute
Options			OOOX ooo XOOO (11)	Gate Options
Vibrator	NONE	Marker Lights	LED - 13 PR TOP & BOTTOM	
Mudflaps	STD + ACROSS REAR (1)	MMTS	BELOW RAIL - LED	
		Apron	NONE	

CHASSIS SPECIFICATIONS					
Model	TRIAXL-2 FIXED-FRONT LIFT	ABS	2S/1M	Tire Carrier	NONE
Beam Mat'l	ALUMINUM			Landing Gear	2 SPEED JOST AX150
Length	34'				D/S CRANK
Width	96"	Independ. Susp(s)		Chassis Lights	NONE
Hoist	85-265 (2)(10)			Elec Coupler	7 WAY + ISO 7 WAY LABELED
Chassis Neck	STD	Distance:			AUXILIARY (2)
King Pin Setting	18"	From:		Hyd Tank	NONE
5th Whl Plate	3/8" W/ 3/8"X 3" X 7" MOUNT	Controls		Hyd Hose Fitting	WINGNUT
5th Whl Ht	50"			Hyd Hose Length	108"
Overhang	6"	Location		Tow Hooks	TWO-ONE EACH SIDE
Rear Axle Setting	21.5"	Axle(s)		Paint	BLACK SOFTCOAT
K/P To Rear Axle	411.5"	Accessories			
Suspension	AAT30K / E3-2 L LIFT-E1 (3)(5)	Brakes		Chassis	CHASSIS REAR CM: TAPERED
Susp Control	FRAME + ELEC CC (4)(9)	Drums		Options:	W/ DIAMOND PLATE COVER
Susp Spacing	52" - 52" (6)	Hubs			
Susp Options	GALVANIZED HANGERS	Wheels			
Springs	AIR				
Axles	TP SPINDLES	Tires			
Accessories	NONE				
Brakes	16-1/2" x 7"				
Drums	CAST				
Hubs	10 STUD STEEL				
Wheels	8.25 x 24.5 6HP/6DB				
Tires	11R 24.5 R250 ED 16PLY BS				

REMARKS:

-
1. BLACK RUBBER FLAP AHEAD OF AXLE #1 IN THE CENTER. INSTALL 4" FORWARD OF STANDARD POSITION.

 2. ADD JUNCTION BOX @ INSIDE FRAME RAIL W/ 7 WIRE FROM AUXIL PLUG IN TO JUNCTION BOX

 3. RIGHT WEIGH OIL FILLED GAUGE (KG) (FLUSH) ON FRONT CHASSIS CROSSMEMBER.

 4. WIRED TO AUXILIARY ISO 7 WAY PLUG

 5. HEIGHT CONTROL VALVE ON AXLE #2.

 6. LIFT AXLE TO BE CONTROLLED THROUGH FRAME SWITCH & ELEC CC (WIRED TO AUX 7 WAY PLUG) AND TO HAVE BRAKE RELEASE (LIFT AXLE TO SPIN FREELY).

 7. ALL FRAME SWITCHES TO BE IN POLY BOX ON D/S NEAR LANDING GEAR.- AIR IN THE BOX **CHANGE 1**

 8. PLASTIC INSULATORS BETWEEN WHEEL/DRUM & WHEEL/HUB ALL AXLES.

 9. INSTALL CROSSOVER KITS WEIGHT: 14,036

 10. NO OUTSIDE ACCESS OR FLAP ON OUTSIDE OF BULKHEAD FOR HOIST-ONLY ON INSIDE DOGHOUSE.

 11. LED BACK UP LIGHTS WIRED TO AUXILIARY ISO 7 WAY PLUG

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.