



**A017644**  
**VIN: 43269**

**SALES | RENTALS | PARTS | SERVICE**

<b>Allentown, PA:</b>	800-383-8894	<b>Jacksonville, FL:</b>	800-828-3055
<b>Baltimore, MD:</b>	888-601-7500	<b>Little Rock, AR:</b>	833-424-8944
<b>Boston, MA:</b>	800-854-5310	<b>Portland, ME:</b>	800-325-4253
<b>Concord, NC:</b>	800-438-2250	<b>Richmond, VA:</b>	866-839-3495
<b>Delmar, DE:</b>	866-486-1400	<b>Scranton, PA:</b>	800-569-1400
<b>Des Moines, IA:</b>	888-673-5011	<b>Springfield, MA:</b>	800-854-5306
<b>Elkton, MD:</b>	800-544-7127	<b>Voorhees, NJ:</b>	866-315-0235

HaleTrailer.com | @haletrailer

**800-232-6535** \*FINANCING AVAILABLE

**Model:** AC-20-AR  
**Capacity in tons:** 20



**1. TONGUE**

Pintle eye Adjustable pintle eye (3" ID) with 48" chain and grab hooks  
 Tongue 5'-6" with lockable tool box with aluminum diamond plate lid - move hinge 4" forward  
 Drop leg 2-speed, 50,000# crank down dual landing leg, mounted to main beams and headboard  
 Electrical receptacle Seven pin connector  
 Headboard 8" high full width

**2. DECK**

Deck section design One piece tongue, main beam and beavertail (cold formed)  
 Deck section length 30'-0" (24'-0" flat with 6'-0" beavertail)  
 Deck section width 8'-6"  
 Loaded deck height 32-1/4"  
 Flooring 1-1/2" apitong with individual wheel wells  
 Lash rings 16 total -  
 6 each side on flat deck (straight style), 12 total  
 1 each side on top of main beams right behind the headboard (swings front to back) (straight style), 2 total  
 1 each side on beavertail (straight style), 2 total  
 Mainbeams 12" deep hi-tensile x 22#  
 Crossmembers 6" deep hi-tensile  
 Sidemembers 8" deep hi-tensile  
 Beavertail 6'-0" Double break with wood flooring full width  
 Ramps 38" wide x 6'-0" long air ramps with wood flooring, stored vertically with lock bar

**3. RUNNING GEAR**

Number of axles 2  
 Axle capacity 25,000#, full width track  
 Brakes 12-1/4" x 7-1/2" air with 2S/1M ABS. Spring brakes on both axles.  
 Wheels Steel disc with oil seals (6.75 x 17.5)  
 Tires Eight (8) 215/75R17.5 (H) 16PR radials  
 Suspension Use valve stem extensions on inside wheels  
 44,800# Hutch spring

**4. GENERAL**

Lights and wiring 12 volt LED system (license plate regular), supplied with female 7-way plug on tongue, SUPPLY JUMPER CORD FOR TRUCK  
 Paint Valspar standard Talbert black, R-Cure 800 series paint  
 Additional general specifications Formed step in front of 1st axle both sides of trailer

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.