

# HALE TRAILER BRAKE & WHEEL



Resale Inventory

A017752

VIN: 575162

SALES | RENTALS | PARTS | SERVICE

|                                     |                                       |
|-------------------------------------|---------------------------------------|
| <b>Allentown, PA:</b> 800-383-8894  | <b>Jacksonville, FL:</b> 800-828-3055 |
| <b>Baltimore, MD:</b> 888-601-7500  | <b>Little Rock, AR:</b> 833-424-8944  |
| <b>Boston, MA:</b> 800-854-5310     | <b>Portland, ME:</b> 800-325-4253     |
| <b>Concord, NC:</b> 800-438-2250    | <b>Richmond, VA:</b> 866-839-3495     |
| <b>Delmar, DE:</b> 866-486-1400     | <b>Scranton, PA:</b> 800-569-1400     |
| <b>Des Moines, IA:</b> 888-673-5011 | <b>Springfield, MA:</b> 800-854-5306  |
| <b>Elkton, MD:</b> 800-544-7127     | <b>Voorhees, NJ:</b> 866-315-0235     |

HaleTrailer.com | @haletrailer

**800-232-6535** \*FINANCING AVAILABLE

| Magnitude 55L Plus 26 Air Tridem (Flat Low Deck) (Model: MAG55LP)   |                          |
|---|--------------------------|
|   | Est. Wt.: 25,782# +/- 3% |
| <b>Capacity:</b> 55 tons in 10-foot length with 4 axles close coupled; 55 tons in 16-foot length with single axle spreader - GAWR and tire ratings determine legal payloads |                          |
| <b>Load Base:</b> 10-foot rigid 2-point load centered in deck area with 4 axles close coupled; 16-foot rigid 2-point load centered in deck area with single axle spreader   |                          |
| <b>Framework:</b> All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs  |                          |
| <b>Compatibility:</b> Designed to accept 55/60 rear axle below, spreader and/or 23 inch flip box - none   |                          |
| <b>Gooseneck Design:</b> Hydraulic removable non-ground bearing design  |                          |
| <b>Loaded Fifth Wheel Height:</b> Dual Cam Pawl Arm Assembly with 10 ride height positions (50 inches nominal)  |                          |
| <b>Swing Radius:</b> 102 inches (11 feet 11 inches overall gooseneck length)  |                          |
| <b>Alternate Kingpin:</b> Dual kingpin at 81 inch and 102 inch radius   |                          |
| <b>Flip Box:</b> None   |                          |
| <b>Power Source:</b> Set up for wet line operation  |                          |
| <b>Electrical Receptacle:</b> J560 7-pin connector  |                          |
| <b>Deck Width:</b> 8 feet 6 inches overall (unless optional deck width is selected)   |                          |
| <b>Deck Length:</b> 26 feet clear deck length **Note: If 60 inch axle spread option is selected trailer is over 53 ft in length   |                          |
| <b>Loaded Deck Height:</b> 18 inches with 6 inches ground clearance   |                          |
| <b>Flooring:</b> 2 inch nominal wood - side rails only  |                          |
| <b>Front Ramps:</b> Manual front approach ramps included  |                          |
| <b>Front Bogie Ramp:</b> Included as standard   |                          |
| <b>Extension Brackets:</b> 13 pair - 26 total removable swing type, 2 pair - 4 total heavy duty removable hook-on type (26 swing type, 4 hook-on type on 27 foot deck)      |                          |
| <b>Deck to Bogie Connection:</b> Fixed  |                          |
| <b>Tool Box:</b> 2 Fully covered trays in front of deck between mainbeams with lockable covers.   |                          |
| <b>Crossmembers:</b> Recess last 3 crossmembers in deck   |                          |
| <b>Number of Axles:</b> 3 axles   |                          |
| <b>Axle Capacity:</b> 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.                                    |                          |
| <b>Axle Spread:</b> 54.5 inches (between axles)   |                          |
| <b>Dust Shields:</b> None   |                          |
| <b>Brakes:</b> 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount  |                          |
| <b>Suspension:</b> Air ride   |                          |
| <b>First Axle Lift:</b> None  |                          |
| <b>Third Axle Lift:</b> Air lift  |                          |
| <b>Tires:</b> 275/70R 22.5 OEM standard   |                          |
| <b>Wheels:</b> 8.25 x 22.5 steel disc - hub-piloted   |                          |
| <b>Bolsters:</b> Recessed load bearing between all axles and rear of last axle  |                          |
| <b>Covered Rear Bogie:</b> Weld-on load bearing wheel covers  |                          |
| <b>Rear Bogie Height:</b> 40 7/8 inches to top flange - 36 5/8 inches to top of bolsters  |                          |
| <b>Boom Trough:</b> V-style boom trough with bolt-in V pan  |                          |
| <b>Mechanical Ride Height Control:</b> Mechanical ride height control valve (Whittle Style)   |                          |
| <b>Manual Dump Valve:</b> Installed   |                          |
| <b>Bumper:</b> Heavy duty V-style rear bumper   |                          |
| <b>Width:</b> 8 feet 6 inches   |                          |

|  |  |
|--|--|
| <b>Spreader: None</b>  |  |
| <b>Flip Axle: None standard</b>  |  |
| <b>Dust Shields on Flip Axle: None standard</b>  |  |
| <b>Electrical System:</b> DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes |  |
| <b>Paint: Fontaine standard black polyurethane enamel</b>  |  |
| <b>Lash Rings:</b> 18 pair - 36 total (19 pair - 38 total when 26ft deck is selected)  |  |
| <b>Flag Holders:</b> Flag holders - 1 pair located at front of deck and on rear bumper                                       |  |
| <b>Accent Package: None</b>  |  |
| <b>Liquid Filled Gauge: None</b>   |  |
| <b>VIN Plate:</b> Bilingual VIN plate  |  |
| <b>Registration/Document Holder:</b> Install registration/document holder  |  |

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.