



Resale Inventory A018149

RENTALS | SALES | PARTS | SERVICE

Allentown, PA: 800-383-8894 Jacksonville, FL: 800-828-3055 Baltimore, MD: 888-601-7500 Little Rock, AR: 833-424-8944 Boston, MA: 800-854-5310 Portland, ME: 800-325-4253 Concord, NC: 800-438-2250 Richmond, VA: 866-839-3495 Delmar, DE: Scranton, PA: 866-486-1400 800-569-1400 Springfield, MA: Des Moines, IA: 888-673-5011 800-854-5306 Elkton, MD: 800-544-7127 Voorhees, NJ: 866-315-0235

HaleTrailer.com | @haletrailer f 쭞 🛅 🎯 🛗





	N: 085019	
V	800-232-6535 *FINANCING AVAILABLE	
components	description	
•		
CAPACITY	Heavy Duty Package - 100,000 lbs. GVWR (80,000 in 10' Span Closed)	
OVERALL LENGTH	48' - 80'Extendable Trailer	
OVERALL WIDTH	8' 6"	
KING PIN SETTING	24"	
UPPER COUPLER PLATE	1/4"	
* * 3rd Gladhand Design to Ope	erate Lock and Release on Locking Pins * *	
* * Sign stating Locking Pin Release above 3rd Gladhand * *		
* * Eliminate Box, Valving, and Bracket on Side of Trailer * *		
* * Tapered Front Plate to allow	/ Easier Hook Up for Multiple Trucks * *	
UPPER COUPLER HEIGHT	48"	
BULKHEAD	Removable Steel - 48" - No Side Return	
* * Last Post on Headboards to	Cap Off Headboards * *	
MAINFRAME	26" Fabricated - PreCambered I-Beams	
* * * 11' Front Deck and 37' Rear Deck * * *		
******Insert 3/16" - Approx 33" \/	Vide - Plate Under Top Flange From Flange to Flange to Allow Customer to walk from	
Deck to Deck When Trailer is Extended*****		

SIDE RAILS 6" - 6.5# Per Foot

- * * New Tapered Corner Design * *
 - * * Pipe and Bullet Connection at Connection Points to help maintain squareness *

·	·
FLOOR SILLS	4" I-Beam 12" O.C. STD Pkg Capacity
FLOOR DECKING	1-1/8" Apitong
WINCH TRACK	Steel Slide Entire Length of Drivers Side
WINCHES	12
STRAPS	None
LANDING GEAR	Two Speed
* * Landing Gear Bracing to one	Horizontal Brace from Box to Box * *
SUSPENSIONS	Spring Ride - Fixed - Hutchens - 3 Axles (-388#)
DUMP VALVE	None
SCALES	None
AXLES	(3) 25K Capacity - Type 30 Chambers - Auto Slacks - ABS - Spring Ride
***** 5/8 Wall Axles********	
AXLE SPACING	49"
PARKING BRAKES	3 Axle
DUST SHEILDS	None
WHEELS	11R22.5
ANTI-SAIL MUD FLAPS	On Rear Skirt
STAKE POCKETS	4" Deep - 24" O.C. & 6 Across Front, 3 Across Rear
RUB BAND STEEL	1/4" X 2-1/2"
PIPE SPOOLS	Double
DOCK BUMPERS	Rubber Inboard

TIRE CARRIERS	None	
TOOLBOXES	None	
TOOLBOX TYPE	None	
LIGHTS	Sealed Wiring Harness w/ LED Pkg	
** Wiring to be Rerouted Per Pictures of Competition (Eliminate Welded Brackets to Main Frame Bottom Flange. **		
PAINT	Black	
CUSTOM 1	None	
CUSTOM 2	None	